








*1989 CHEVROLET
G-VAN
RESTORATION
PACKAGE*

[illegible]




CONTENTS

	<u>Page</u>
MODEL SELECTION	<u>2</u>
STANDARD	4
POWERTEAMS	5
SPECIFICATIONS	6
OPTIONAL EQUIPMENT	14
FEATURES TO SELL	17
COLOR AND TRIM	18


	G10/1500 CHEVY VAN/ VANDURA 125-IN. WB			G20/2500 CHEVY VAN/ VANDURA 110-IN WB			G20/2500 CHEVY VAN/ VANDURA 125-IN. WB			G30/3500 CHEVY VAN/ VANDURA 125-IN. WB		
WB (IN.)												
GVWR RANGE (LBS.)												
MAX. PAYLOAD CAP. (LBS.)												
PASS. CAP. STD/OPT												
STD ENGINE/TRANS												
OPT ENGINE/TRANS												
MODEL NUMBER												

110	4900	1192	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11005 ZW9
110	5350	1619	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11005 ZW9 w/ F60/ G50
110	5600	1845	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11005 ZW9 w/ F60/ G50
110	6000	2231	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11005 ZW9 w/ J55/F60 G50
125	4900	1047	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11305 ZW9
125	5350	1474	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11305 ZW9 w/ G50
125	5600	1718	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11305 ZW9 w/ F60/ G50
125	6000	2086	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4	G11305 ZW9 w/ J55/F60/ G50
WB (IN.)	GVWR RANGE (LBS.)	MAX. PAYLOAD CAP. (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
110	6600	2810	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4 6.2L V8/M4/A4	G21005 ZW9
110	6600	2314	1 2	6.2L V8/M4	6.2L V8/A4	G21005 ZW9
WB (IN.)	GVWR RANGE (LBS.)	MAX. PAYLOAD CAP. (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	6600	2667	1 2	4.3L V6/M4	4.3L V6/A4 5.0L V8/M4/A4 5.7L V8/A4 6.2L V8/M4/A4	G21305 ZW9
125	6600	2206	1 2	6.2L V8/M4	6.2L V8/A4	G21305 ZW9
WB (IN.)	GVWR RANGE (LBS.)	MAX. PAYLOAD CAP. (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER


WHEELBASE) The G10/1500 Chevy Van/Vandura 110-in. wheelbase is the base full-size cargo van model. A variety of GVWRs and powerteams are offered.		G10/1500 CHEVY VAN/ VANDURA (125-IN. WHEELBASE) The G10/1500 Chevy Van/Vandura 125-in. wheelbase model offers increased cargo length and volume when compared to the 110-in. wheelbase G10/1500 model.		G20/2500 CHEVY VAN/VANDURA (110-IN. WHEELBASE) The G20/2500 Chevy Van/Vandura 110-in. wheelbase model offers a higher GVWR than the G10/2500 series and is available with a variety of powerteams.		G20/2500 CHEVY VAN/VANDURA (125-IN. WHEELBASE) The G20/2500 Chevy Van/Vandura 125-in. wheelbase model offers increased cargo length and volume when compared to the 110-in. G20/2500 model.		G30/3500 CHEVY VAN/VANDURA The G30/3500 Chevy Van/Vandura offers the highest GVWRs in the G-Chevy Van/Vandura cargo van series. It is only offered in a 125-in. wheelbase version.	
---	--	--	--	--	--	---	--	--	--



A low-back driver's side front bucket seat with Vinyl trim is standard. This seat can be replaced with an optional high back seat with either Vinyl or Custom Vinyl trim.



This option consists of a low-back driver's side front bucket seat and a low back passenger's side front bucket seat both with Vinyl trim.



This option consists of a high back driver's side front bucket seat and a high back passenger's side front bucket seat both available with either Vinyl or Custom Vinyl trim.

SIDE DOOR APPLICATIONS

**STANDARD: CHOICE OF
SLIDING SIDE DOOR (YA2) OR
SIDE SWING OUT DOORS (E24)**

All Chevy Van/Vandura models are offered with a choice of a standard sliding side door (RPO YA2) or side swing out doors (RPO E24).
(Available at no extra cost.)

TRIM LEVELS

STANDARD

The Chevy Van/Vandura Cargo Van is offered only in a Standard trim level. The Standard trim includes an impressive level of features to meet the needs of the full-size cargo van buyer.

The Chevy Van/Vandura is designed to offer buyers a high level of standard comfort and convenience features when purchasing a standard-level van.

The following features are standard:



Some equipment shown may be optional or extra cost.

POWERTEAM/CHASSIS

- 4.3-liter V6 engine with Electronic Fuel Injection (EFI) is standard on models below 8600 lbs. GVWR. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm.
- 5.7-liter V8 engine with Electronic Fuel Injection (EFI) is standard on 8600 lb GVWR models. It produces 185 horsepower @ 4000 rpm and 295 lb. ft. of net torque @ 2400 rpm.

- A 4-speed manual overdrive transmission with floor-mounted shift lever is standard on all G10/1500 and G20/2500 models. Either a 4-speed automatic overdrive transmission or a 3-speed automatic transmission with steering column mounted shift lever is standard on G30/3500 series models, depending on their GVWR (see Powerteams section for details).
- Front suspension is an independent coil spring design.

- Rear suspension is a two-stage multi-leaf spring design.
- Power front disc/rear drum brakes.
- Power steering.
- All-welded integral body-frame construction.
- 22.0-gallon fuel tank.
- Heavy-duty front and rear shock absorbers, on G20/2500 and G30/3500 models.

EXTERIOR

- Front and rear bumpers painted silver.
- Molded plastic grille and front lamp bezels painted light argent. Vandura grille has dark argent air intake areas.
- Single rectangular headlamps.
- Bright metal hub caps with black trim.

- White painted wheels.
- All-season steel-belted radial tires (G10/1500 and G20/2500 Series).
- Full-size spare tire and wheel on G10/1500 Series. (Spare wheel only on G20/2500 and G30/3500 Series).
- RH and LH white painted below eye-line mirrors with adjustable heads.

- Single electric low-note horn.
- Tools include mechanical jack and wheel wrench.
- Undercoating on body rocker panels, step panels and wheel housings.

INTERIOR

- LH padded armrest.
- Front bucket adjustable driver's seat with all-vinyl trim.
- LH coat hook.
- Safety step pads on front and rear side door step panels.
- Latex foam rubber door seals.
- Two dome lamps with front door-actuated switches.

- Floor-covering consists of embossed black rubber mat on driver's side.
- LH padded, color-keyed sunshade.
- Gages include speedometer, odometer, fuel level, oil pressure, voltmeter, engine temperature, and trip odometer.
- Steering column with anti-theft locking feature.
- Deluxe outside air heater and defogger.

- Mystic-colored perforated hardboard headliner in driver's area.
- Stowage box with latched door on front face of instrument panel extension.
- Parcel tray on top surface of instrument panel extension, includes beverage holder provisions.
- Spare tire carrier on RH rear side.

MODEL NUMBER	G11005	G11305	(110-1R: WD)								(125-1R: WD)								G31305
			GAS				DIESEL				GAS				DIESEL				
			G21005				G21305				G21005				G21305				
SUSPENSION (STD)																			
Maximum Available Payload (lbs.) ¹	1185	1038	2810	2302	2667	2194							2901						
Total GVWR (lbs.)	4900	4900	6600	6600	6600	7100							7100						
FRONT: GAWR (lbs.)	2620	2620	3400	3500	3400	3670							3400						
REAR: GAWR (lbs.)	2400	2400	3400	3400	3400	3980							3980						
FRONT: Suspension Type	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring							Ind. Coil Spring						
Standard Spring Capacity (lbs.)	2620	2620	3400	3500	3400	3670							3400						
REAR: Suspension Type	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf							Semi-Elliptic 2-Stage Multi-Leaf						
Standard Spring Capacity (lbs.)	2400	2400	3400	3400	3400	4200							4200						
Leaves Per Spring	4	4	5	5	5	5							5						
Leaf Total Thickness (in.)	1.57	1.57	1.97	1.97	1.97	2.03							2.03						
FRONT: Shock Absorber Piston Diameter (mm) STD/OPT	25/32	25/32	32/—	32/—	32/—	32/—							32/—						
Stabilizer Bar Diameter (in.) STD/OPT	—/1.06	—/1.06	—/1.06	—/1.06	—/1.06	—/1.06							—/1.06						
REAR: Shock Absorber Piston Diameter (mm) STD/OPT	25/32	25/32	32/—	32/—	32/—	32/—							32/—						
FRONT: Axle Type	—	—	—	—	—	—							—						
Make	—	—	—	—	—	—							—						
Maximum Capacity (lbs.)	3400	3400	3400	3500	3400	3675							3900						
Standard Hub Locks	—	—	—	—	—	—							—						
Pinion/Ring Gear Type	—	—	—	—	—	—							—						
REAR: Axle Type	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating							Semi-Floating						
Make	GM	GM	GM	GM	GM	GM							GM						
Maximum Capacity (lbs.)	3500	3500	3500	3500	3500	5700							5700						
Pinion/Ring Gear Type	Hypoid	Hypoid	Hypoid	Hypoid	Hypoid	Hypoid							Hypoid						
Ratio	See Powerteams	See Powerteams	See Powerteams	See Powerteams	See Powerteams	See Powerteams							See Powerteams						
Standard Tires	Tubeless SBR P195/75R15	Tubeless SBR P195/75R15	Tubeless SBR P225/75R15	Tubeless SBR P225/75R15	Tubeless SBR P225/75R15	Tubeless Steel-Belted Radial P235/75R15							Tubeless Bias Ply 8.75-16.5-E						
Tire Capacity (lbs. each) Front/Rear	1342	1342	1703	1843	1703	1843							1990/2680						
Inflation (PSI)	35	35	35	35	35	35							75						
Wheel Size (in.)	15 x 6.00 JJ	15 x 6.00 JJ	15 x 6.00 JJ	15 x 6.00 JJ	15 x 6.00 JJ	16.5 x 6.75							16.5 x 6.75						
Wheel Capacity (lbs. each)	1585	1585	1984	1984	1984	2680							2680						
Bolt Holes	5	5	5	5	5	8							8						
Bolt Circle Diameter (in.)	5	5	5	5	5	6.5							6.5						
Offset (in.)	.34	.34	.14	.14	.14	1.35							1.35						
Revolutions per mile @ 45 MPH	787	787	737	722	737	712							712						

MODEL NUMBER		G11005				G11305				GAS	DIESEL	GAS	DIESEL	GAS	DIESEL
										G21005		G21305		G31305	
										B3J		B3J		B3J	
SUSPENSION (OPT)															
Option	F60/ G50	F60/ G50	J55/ F60/ G50	F60/ G50	F60/ G50	J55/ F60/ G50	F60/ G50	F60/ G50	J55/ F60/ G50	G50	G50	G50	G50	G50	C6P
Maximum Available Payload (lbs.) ¹	1587	1830	2231	1474	1718	2086				2810	2314	2667	2206		4178
Total GVWR (lbs.)	5350	5600	6000	5350	5600	6000				6600	6600	6600	6600		8600
FRONT: GAWR (lbs.)	2684	2906	3166	2684	2906	3166				3400	3500	3400	3670		3900
REAR: GAWR (lbs.)	2684	2906	3166	2684	2906	3166				3400	Ind. Coil Spring	3400	3400	Ind. Coil Spring	5360
FRONT: Suspension Type	Ind. Coil Spring			Ind. Coil Spring			Ind. Coil Spring			Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring
Standard Spring Capacity (lbs.)	3400			3400			3400			3400	3500	3400	3670		3900
REAR: Suspension Type	Semi-Elliptic 2-Stage Multi-Leaf			Semi-Elliptic 2-Stage Multi-Leaf			Semi-Elliptic 2-Stage Multi-Leaf			Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf		Semi-Elliptic 2-Stage Multi-Leaf
Standard Spring Capacity (lbs.)	3400			3400			3400			3400	3400	3400	3400		5400
Leaves Per Spring	5			5			5			5	5	5	5		8
Leaf Total Thickness (in.)	1.97			1.97			1.97			2.03	2.03	2.03	2.03		3.00
FRONT: Shock Absorber Piston Diameter (mm)	25/32			25/32			25/32			32/—	32/—	32/—	32/—		32/—
Stabilizer Bar Diameter (in.) STD/OPT	—/1.06			—/1.06			—/1.06			—/1.06	—/1.06	—/1.06	—/1.06		1.06/—
REAR: Shock Absorber Piston Diameter (mm)	25/32			25/32			25/32			32/—	32/—	32/—	32/—		32/—
FRONT: Axle Type	—			—			—			—	—	—	—		—
Make	—			—			—			—	—	—	—		—
Maximum Capacity (lbs.)	3400			3400			3400			3400	3500	3400	3675		3900
Standard Hub Locks	—			—			—			—	—	—	—		—
Pinion/Ring Gear Type	—			—			—			—	—	—	—		—
REAR: Axle Type	Semi-Floating			Semi-Floating			Semi-Floating			Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating		Semi-Floating
Make	GM			GM			GM			—	—	—	—		GM
Maximum Capacity (lbs.)	3500			3500			3500			3500	3500	3500	3500		5700
Pinion/Ring Gear Type	Hypoid			Hypoid			Hypoid			Hypoid	Hypoid	Hypoid	Hypoid		Hypoid
Ratio	See Powerteams			See Powerteams			See Powerteams			See Powerteams	See Powerteams	See Powerteams	See Powerteams		See Powerteams
Standard Tires	Tubls. SBR P195/75R15	Tubls. SBR P205/75R15	Tubls. SBR P215 75R15	Tubls. SBR P195/75R15	Tubls. SBR P205/75R15	Tubls. SBR P215/75R15	Tubls. SBR P225/75R15	Tubls. SBR P235/75R15	Tubls. SBR P235/75R15	TbIs SBR P225/75R15	TbIs SBR P235/75R15	TbIs SBR P235/75R15	TbIs SBR P235/75R15		Tubeless Nylon Bias Ply 8.75-16.5-E
Tire Capacity (lbs. each)	1342	1453	1583	1342	1453	1583	1703	1843	1703	1703	1843	1843	1843		1990/2680
Inflation (PSI)	35	35	35	35	35	35	35	35	35	35	35	35	35		75
Wheel Size (in.)	15 x 6.00JJ			15 x 6.00JJ			15 x 6.00JJ			15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ		16.5 x 6.75
Wheel Capacity (lbs. each)	1585			1585			1585			1984	1984	1984	1984		2680
Bolt Holes	5			5			5			5	5	5	5		8
Bolt Circle Diameter (in.)	5			5			5			—	—	—	—		6.5
Offset (in.)	.34			.34			.14			.14	.14	.14	.14		1.35
Revolutions per mile @ 45 MPH	787	769	753	787	769	753	737	722	737	737	722	722	722		712

MODEL NUMBER	G11005-G11305		GAS		DIESEL		GAS		DIESEL	
			G21005-G21305		B3J		G31305		G31305/C6P	
STEERING										
Type	Integral Power		Integral Power		Integral Power		Integral Power		Integral Power	
Steering Ratio	17.2:1		17.2:1		17.2:1		17.2:1		17.2:1	
Turning Diameter: Curb-To-Curb (ft.) Wall-To-Wall (ft.)	41.3 - 45.9 42.7 - 47.5		41.3 - 46.0 42.7 - 47.5		48.5 49.8		48.5 49.8			
BRAKES										
GVWR	4900 5350/5600		6000		6600		6600		7100	
Type	Vac. Power Front Disc/ Rear Drum		Vac. Power Front Disc/ Rear Drum		Vac. Power Front Disc/ Rear Drum		Hyd. Power Front Disc/ Rear Drum		Vac. Power Front Disc/ Rear Drum	
Booster (Diaphragm Diameter) (in.)	9.5 x 8.0 Single		9.5 x 8.0 Tandem		9.5 x 8.0 Tandem		—		9.5 x 8.0 Tandem	
Front Rotor Size (Diameter x Thickness) (in.)	11.86 x 1.29		11.86 x 1.29		11.86 x 1.29		11.86 x 1.29		12.50 x 1.28	
Front Facing Contact Per Axle (sq. in.)	37.63		37.63		37.63		37.63		42.98	
Rear Drum Size (Diameter x Width) (in.)	11.0 x 2.0		11.0 x 2.0		11.15 x 2.75		11.15 x 2.75		13.0 x 2.5	
Rear Facing Contact Per Axle (sq. in.)	74.34		107.42		107.42		107.42		116.73	
Parking Brake	Cable To Rear Wheels		Cable To Rear Wheels		Cable To Rear Wheels		Cable To Rear Wheels		Cable To Rear Wheels	

MODEL	MODEL NUMBER	VANDURA (110-IN. AND 125-IN. WB)		VANDURA (110-IN. AND 125-IN. WB)		G30/3500 CHEVY VAN/ VANDURA	
		GAS	DIESEL	GAS	DIESEL	GAS	DIESEL
ELECTRICAL		G21005-G21305		B3J		B3J	
Engine Std./Opt.	4.3L V6/5.0L V8 ¹	4.3L V6/ 5.0L V8/ 5.7L V8	6.2L V8	4.3L V6	5.7L V8	6.2L V8	6.2L V8
Standard Battery: Cold Cranking Amps @ 0°F @ -20°F	525 390	525 390	Two at 540 Each 410 Each	525 390	525 390	Two at 540 Each 410 Each	Two at 540 Each 410 Each
Reserve Capacity Minutes @ 80°F	90	90	115	90	90	115	115
Optional Battery:	UA1	UA1	—	UA1	UA1	—	—
Cold Cranking Amps @ 0°F @ -20°F	630 490	630 490	—	630 490	630 490	—	—
Reserve Capacity Minutes @ 80°F	115	115	—	115	115	—	—
Standard Generator: Max Capacity (Amps)	85	85	66	85	85	66	66
Max Watts @ 12 Volts	1020	1020	792	1020	1020	792	792
Nominal Amp @ Idle (Approx.)	30	30	23	30	30	23	23
Drive Pulley Ratio	2.7:1	2.7:1	3.1:1	2.7:1	2.7:1	3.1:1	3.1:1
Model Number	CS130	CS130	12-SI-100	CS130	CS130	12-SI-100	12-SI-100
Optional Generator:	w/C60 or C/69	w/C60 or C69	—	w/C60 or C69	w/C60 or C69	—	—
Max Capacity (Amps)	100	100	—	100	100	—	—
Max Watts @ 12 Volts	1200	1200	—	1200	1200	—	—
Nominal Amp @ Idle (Approx)	54	54	—	54	54	—	—
Drive Pulley Ratio	3.1:1	3.1:1	—	3.1:1	3.1:1	—	—
Model Number	CS130	CS130	—	CS130	CS130	—	—

¹5.0L/305 V8 with manual transmission uses 430CCA battery @ 0°F, 330CCA @ -20°F, and has a Reserve Capacity of 90 min. @ 80°F.

MODEL	G10/1500 CHEVY VAN/VANDURA		G20/2500 CHEVY VAN/VANDURA		G30/3500 CHEVY VAN/VANDURA	
MODEL NUMBER	G11005-G11305		G21005-G21305		G31305	
STANDARD COOLING SYSTEM						
Engine	4.3L V6	5.0L V8	4.3L V6	5.0L V8	6.2L V8	5.7L V8 6.2L V8
Standard Radiator Thickness (in.)	.93	.98	.93	.98	1.57	.98 1.57
Total System Cap. (gal.)	3.4	4.2	3.4	4.2	6.3	4.2 6.2
Standard Fan (No. Blades x Diameter x Pitch)	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	5 x 20 x 2.87	5 x 20 x 2.87
OPTIONAL COOLING SYSTEMS						
Engine	4.3L V6	5.0L V8	4.3L V6	5.0L V8	6.2L V8	5.7L V8 6.2L V8
AUTOMATIC TRANS.	MX0	MX0	MX0	MX0	MX0	MX1 MX1
Radiator Thickness (in.)	.93	.98	.93	.98	1.57	.98 1.57
Total Systems Cap. (gal.)	3.4	4.2	3.4	4.2	6.2	4.2 6.2
Fan (No. Blades x Diameter x Pitch)	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	5 x 20 x 2.87	5 x 20 x 2.87
OPT. AIR CONDITIONING	C60 ²	C60	C60 ²	C60	C60	C60 •C60
Radiator Thickness (in.)	.93	.98	.93	.98	1.57	1.57 2.17
Total System Cap. (gal.)	3.3	4.2	3.3	4.2	6.2	4.2 6.2
Fan (No. Blades x Diameter x Pitch)	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 20 x 2.87	5 x 20 x 2.87
OPT. H.D. RADIATOR AND TRANS. OIL COOLER	V02 ³	V02 ³	V02 ³	V02 ³	V02 ³	V02 ³
Radiator Thickness (in.)	1.34	1.57	1.34	1.57	1.57	1.57 2.17
Total System Cap. (gal.)	3.4	4.2	3.4	4.5	6.2	4.5 6.2
Fan (No. Blades x Diameter x Pitch)	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 20 x 2.87	5 x 20 x 2.87

¹ N/A In California

² C60 N/A LB4 Engine w/MM7 Transmission on G10/G20 Models

³ Reqs. MX0 Trans. and V05 Cooling. C60, or C69 Air Conditioning. (LB4 Engine Reqs. KC4 Cooler) (Included with Z82 Trailering).

calculating payload capacity, gross axle weight, axle reserve capacity, gross vehicle weight and total reserve capacity.

For more information on calculating these capacities, consult the “FORMS” section of this book.

MODEL WEIGHTS		WEIGHT (lbs.)		
MODEL/BODY		FRONT		TOTAL
		FRONT	REAR	TOTAL
G11005		2242	1651	3893
G11305		2304	1728	4032
G21005		2264	1682	3946
G21005/B3J		2676	1749	4425
G21305		2327	1763	4090
G21305/B3J		2729	1817	4546
G31305		2558	2045	4603
G31305/C6P		2558	2045	4603
G31305/C6P/B3J		2873	2085	4958




CURB WEIGHTS		WEIGHT (lbs.)		
MODEL/BODY		FRONT		TOTAL
		FRONT	REAR	TOTAL
G11005		2137	1611	3748
G11305		2193	1696	3889
G21005		2158	1638	3796
G21005/B3J		2570	1705	4275
G21305		2216	1724	3940
G21305/B3J		2618	1778	4396
G31305		2447	2006	4453
G31305/C6P		2447	2006	4453
G31305/C6P/B3J		2762	2046	4808

***2	0	0	0
***4	5	2	2
	9	4	4
***7	0	0	0

PAINT WEIGHTS				
CODE	CONDITION	WEIGHT (lbs.)		
		FRONT	REAR	
ZY1		0	0	
ZY3		5	8	
ZY4		5	8	


AA3	0	0	0	—A—
AD8	0	2	2	
AJ1	0	0	0	
AU3	6	1	1	
A01	0	0	0	
A02	0	0	0	
A07	7	54	54	
G11005-21005				
G11305-21305-				
31305	10	64	64	
G11005-21005	5	17	17	
G11305-21305-				
31305	5	19	19	
w/o E24	—3	15	15	
G11005-				
21005	5	7	7	
G11305-				
21305-30	5	6	6	
w/E24				
G11005-				
21005	2	3	3	
G11305-				
21305-30	3	3	3	
G11005-21005	1	1	1	
G11305-				
21305-30				
w/o A07	9	11	11	
w/A07	1	11	11	
G11005-21005	—3	15	15	
G11305-				
21305-30	—4	16	16	
G11005-21005	4	7	7	
G11305-				
21305-30	5	6	6	
G11005-21005	137	70	70	
G11305-				
21305-31305	146	62	62	
—B—				
B3D	0	0	0	
B30	4	5	5	
B32	5	0	0	
B84	4	8	8	
B96	1	1	1	
—C—				
CD4	1	0	0	
C36	11	12	12	
G11005-21005				
G11305-21305-				
31305	12	10	10	
w/LB4	56	—6	—6	
w/o LH6/LL4/				
LB4	54	—4	—4	
w/LH6	80	—4	—4	
w/LL4	87	—4	—4	
w/o LH6/LL4	58	36	36	
w/LH6	82	37	37	
w/LL4	89	37	37	
—D—				

F59	—F—	21	0	NA5	—N—	0	0	YAR	—Y—	0
F60		2	0	NA6		0	0	YA2		0
				NK3	G11305-	-2	0	YCE		3
					21305-30	-1	0	YCU		9
GQ1	—G—	0	0		G11005-21005	-19	107	YCV		9
GT4		0	3	NL7	w/o LH6/LL4	-23	131	YCW		8
		0	0		w/LH6/LL4	1	0	YET		0
GT5		0	0	N31		12	17	YEU		0
GU5		0	1	N67	G10	2	3	YEV		0
GU6		0	0		G20	2		YF5		0
G50		0	21		—P—	2	3	YSD		5
		0	3	PF3	G10	-13	-15	YTH		0
G80		0	7	P17	G20	0	2	YVD		14
	—J—	12	9						—Z—	
J55					—T—			ZAR		0
				TR9		1	1	ZCE		1
KC4	—K—	5	-1	TT5		3	0	ZCU		5
K05		1	0	TVR		1	1	ZCV		5
					—U—			ZCW		5
LB4	—L—	0	0	UA1	w/o LB4	5	0	ZET		-5
	G10-20	-154	-23		w/LB4	4	0	ZEU		-5
L03		147	-4	UM6		9	3	ZEV		-5
	G11305-21305	149	-4	UM7		4	0	ZQ2		13
L05		125	11	UU9		2	0	ZQ3		10
LH6	G20	0	0	UX1		4	0	ZTH		-7
LL4		0	0	U35		0	0	ZVD		-10
		0	0	U37		0	0	Z72		-5
	—M—			U63		5	2	Z82	G21005	23
MM7	w/LB4	17	10	U66		1	3		w/o LH6	7
	G11005-21005	0	0		—V—				w/LH6	78
MX0		14	22	V02		6	-1		G21305	21
	w/L03	-9	15	V05	w/o MX0	6	-1		w/LH6	4
	w/LH6				w/MX0	3	-1		G31305	0
G11005 w/LB4		17	19	V22		5	-1		w/o LL4	79
w/o YF5				V31	G11305-				w/LL4	81
w/LB4		28	19		21305-30	11	-3			
w/YF5		16	20	V37	G11005-21005	12	-4			
G11305-21305		3	5			0	0			
w/L03		-12	5		—X—					
w/L05				XAR		0	0			
w/LH6	G11305 w/LB4	19	17	XCE		3	0			
G11305 w/LB4	w/o YF5	30	17	XCU		9	0			
w/o YF5	w/LB4	28	21	XCV		9	0			
w/YF5		30	18	XCW		8	0			
G21005 w/LB4		-6	-3	XET		0	0			
G21305 w/LB4		-14	-2	XEU		0	0			
G31305 w/L05	w/LL4			YTV		0	0			




CONTENTS


	<u>Page</u>
MODEL SELECTION	2
STANDARD	4
BEAUVILLE/RALLY STX	5
POWERTEAMS	6
SPECIFICATIONS	8
OPTIONAL EQUIPMENT	16
FEATURES TO SELL	19
COLOR AND TRIM	20
TRAILERING	26




G10/1500 SPORTVAN/RALLY




G10/1500 BEAUVILLE/ RALLY STX




G20/2500 SPORTVAN/RALLY



G20/2500 BEAUVILLE/ RALLY STX



G30/3500 SPORTVAN/RALLY



(IN.)	(LBS.)	(LBS.)	STD/OPT	ENGINE/TRANS	ENGINE/TRANS	MODEL NUMBER
110	5600	1542	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4	G11006 ZW9
116	6000	1918	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4	G11006 ZW9
WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	5600	1386	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G11306 ZW9
125	6000	1762	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G11306 ZW9
WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	5600	1250	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G11306 E94
125	6000	1626	5	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G11306 E94
WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	6600	2354	5/8	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G21306 ZW9
125	6850	2106	5/8	6.2L V8/M4	6.2L V8/A4	G21306 ZW9
WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	6600	2218	5/8	4.3L V6/M4	4.3L V6/A4 5.0L V8/A4 5.7L V8/A4	G21306 E94
125	6850	1970	5/8	6.2L V8/M4	6.2L V8/A4	G21306 E94
WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	7400	2426	12	5.7L V8/A4	—	G31306 ZW9

(110-IN. WHEELBASE)

The G10/1500 Sportvan/Rally 110-in. wheelbase is the base full-size passenger van model and the only 110-in. wheelbase model in the Sportvan/Rally line. A variety of GVWR's and powerteams are offered.

G10/1500 SPORTVAN/RALLY (125-IN. WHEELBASE)

The G10/1500 Sportvan/Rally 125-in. wheelbase model offers increased cargo length and volume when compared to the 110-in wheelbase G10 model.

G10/1500 BEAUVILLE/RALLY STX

The G10/1500 Beauville/Rally STX offers additional trim, comfort and convenience features when compared to the G10/1500 Sportvan/Rally models.

G20/2500 SPORTVAN/RALLY

The G20/2500 Sportvan/Rally offers increased GVWR capacity when compared to the G10/1500 Sportvan/Rally models.

G20/2500 BEAUVILLE/RALLY STX

The G20/2500 Sportvan/Rally STX offers additional trim, comfort and convenience features when compared to the G20/2500 Sportvan/Rally models.

G30/3500 SPORTVAN/RALLY

The G30/3500 Sportvan/Rally offers increased GVWR's when compared to the G10/1500 and G20/2500 models.

*Total available for passengers, cargo, and equipment.

RALLY STX
The G30/3500 Beauville/Rally STX offers additional trim, comfort and convenience features when compared to the G30/3500 Sportvan/Rally models.

G30/3500 SPORTVAN/ RALLY (C6P)

The G30/3500 Sportvan/Rally (C6P) offers an increased GVWR when compared to the regular G30/3500 models.

G30/3500 BEAUVILLE/RALLY STX (C6P)


The G30/3500 Beauville/Rally STX (C6P) offers additional trim comfort and convenience features when compared to the G30/3500 Sportvan/Rally models.

WB (IN.)	GVWR (LBS.)	MAX. PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	MODEL NUMBER
125	7400	2290	12	5.7L V8/A4	—	G31306 E94
G30/3500 HEAVY-DUTY SPORTVAN/RALLY (C6P)						
125	8600	3865	5/8/12	5.7L V8/A3	6.2L V8/A3	G31306 ZW9 (C6P)
125	8600	3561	5/8/12	6.2L V8/A3	—	G31306 ZW9 (C6P) B3J
G30/3500 HEAVY-DUTY BEAUVILLE/RALLY STX (C6P)						
125	8600	3765	5/8/12	5.7L V8/A3	6.2L V8/A3	G31306 E94 (C6P)
125	8600	3425	5/8/12	6.2L V8/A3	—	G31306 E94 (C6P) B3J


*Total available for passengers, cargo, and equipment.

SEATING ARRANGEMENTS


STANDARD ON G10/1500 AND G20/2500 MODELS AND G30/3500 MODELS WITH C6P: 5-PASSENGER SEATING




STD ON G30/3500 MODELS WITHOUT C6P, OPTIONAL ON G30/3500 MODELS WITH C6P: 12-PASSENGER (AQ4)



OPTIONAL ALL MODELS: 5-PASSENGER SEATING WITH TRAVEL BED REPLACING CENTER SEAT (B6S)




OPTIONAL ON G10/1500 AND G20/2500 MODELS ONLY: 8-PASSENGER WITH TRAVEL BED REPLACING THIRD SEAT (B6S/AQ3)



SIDE DOOR CHOICE OF SLIDING SIDE DOOR (STD) OR SIDE SWING OUT DOORS (TR4)

OPTIONAL ON G20/2500 AND G30/3500 MODELS ONLY: 8-PASSENGER SEATING (AQ3)



TRIM LEVELS

STANDARD

The Sportvan/Rally Passenger Van line consists of two models: Standard and Beauville/STX. The Standard Sportvan/Rally is the base trim level emphasizing value.

BEAUVILLE/STX

The Beauville/STX offers additional trim, comfort and convenience features when compared to the Standard trim level.



Some equipment shown may be optional or extra cost.

the standard trim level of the Sportvan/Rally series is designed to offer buyers a high level of standard features when purchasing a standard-level van.

The following features are standard:

POWERTEAM/CHASSIS

- 4.3-liter V6 engine with Electronic Fuel Injection (EFI) is standard on G10/1500 and G20/2500 models. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm.
- 5.7-liter V8 engine with Electronic Fuel Injection (EFI) is standard on all G30/3500 models. It produces 195 horsepower @ 4000 rpm and 290 lb. ft. of net torque @ 2400 rpm on models with 7400-lb. GVWRs, and 185 horsepower and 295 lb. ft. of torque on 8600-lb. GVWR models.

- A 4-speed manual overdrive transmission with floor-mounted shift lever on G10/1500 and G20/2500 models. A 4-speed automatic transmission with overdrive and a steering column-mounted shift lever is standard on G30/3500 models with 7400-lb. GVWR, and 3-speed automatic and a steering column-mounted shift lever is standard on G30/3500 models at 8600 lbs. GVWR.

- Front suspension is an independent coil spring design. G30/3500 models include a front stabilizer bar.
- Rear suspension is a two-stage multi-leaf spring design.
- Power front disc/rear drum brakes.
- Power steering.
- All-welded integral body frame construction.
- 22.0-gallon fuel tank.

EXTERIOR

- Front and rear bumpers painted silver.
- Molded plastic grille painted light argent. Single rectangular headlamps.
- Bright metal hub caps with black trim.
- Dual electric high-note and low-note horn.
- White painted wheels.

- All-season steel-belted radial tires G10/1500 and G20/2500 Series only.
- Full-size spare tire and wheel G10/1500 Series only. Spare wheel only on G20/2500 and G30/3500 models.
- RH and LH white painted below eye-line mirrors with adjustable heads.

- Tools include mechanical jack and wheel wrench.
- Undercoating on body rocker panels, step panels and wheel housings.
- Glass includes windshield, front side doors, rear doors, side load door and LH front quarter flip-out glass, and RH and LH rear quarter fixed glass.

INTERIOR

- RH and LH side door and rear seat padded armrests. Door trim panels are painted metal with decorative embossments.
- Five passenger seating with front adjustable high-back bucket seats with all-vinyl trim and a removable 3-passenger bench seat with all-vinyl trim. G30/3500 models w/7400 lb. GVWR feature standard 12-passenger seating, adding a second position middle and rear 4-passenger bench seat with all-

- Safety step pads on front and rear side door step panels.
- Latex foam rubber door seals.
- Front and rear dome lamps with front door-actuated switches.
- Floor-covering consists of embossed black rubber mats over entire floor area and front wheelhousings.
- RH and LH padded, color-keyed sunshades.
- Gages include speedometer, odometer, fuel level, voltmeter, oil pressure, engine temperature and

- 2-spoke steering wheel with anti-theft locking feature in steering column.
- Mystic-colored perforated hardboard headliner in driver's area.
- Parcel tray on top surface of instrument panel extension, includes beverage holder provisions.
- Spare tire carrier on RH rear side.
- Insulation and sound-deadening material under instrument panel,

The Beauville/Rally STX trim level is an optional trim level for the Sportvan/Rally series. It is designed to offer buyers an increased level of comfort and convenience features compared to the Standard trim level.

The following features are standard. Bold type denotes equipment in addition to or replacing that of the Standard trim level.



Some equipment shown may be optional or extra cost.

POWERTeam/CHASSIS

- 4.3-liter V6 engine with Electronic Fuel Injection (EFI) is standard on G10/1500 and G20/2500 models. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm.
- 5.7-liter V8 engine with Electronic Fuel Injection (EFI) is standard on all G30/3500 models. It produces 195 horsepower @ 4000 rpm and 290 lb. ft. of net torque @ 2400 rpm on models with 7400-lb. GVWR and

- 185 horsepower and 295 lb. ft. of torque on 8600 lb. GVWR models.
- A 4-speed manual overdrive transmission with floor-mounted shift lever on G10/1500 and G20/2500 models. A 4-speed automatic transmission with overdrive and a steering column-mounted shift lever on G30/3500 models up to 8600 lbs. GVWR, and 3-speed automatic and a steering column-mounted shift lever on G30/3500 models at 8600 lbs. GVWR.

- Front suspension is an independent coil spring design. G30/3500 models include a front stabilizer bar.
- Rear suspension is a two-stage multi-leaf spring design.
- Power front disc/rear drum brakes.
- Power steering.
- All-welded integral body frame construction.
- 22.0-gallon fuel tank.

EXTERIOR

- Front and rear **chrome** bumpers.
- **Beauville/Rally STX nameplates.**
- Molded plastic grille painted light argent. **Chevy models have bright center bar moldings with body color paint fill.**
- **LH and RH dual rectangular headlamps.**
- Dual electric high-note and low-note horn.
- Bright metal hub caps with black trim.

- White painted wheels.
- All-season steel-belted radial tires G10/1500 and G20/2500 Series only.
- Full-size spare tire and wheel. Spare wheel only on G20/2500 and G30/3500.
- RH and LH white painted below eye-line mirrors with adjustable heads.
- Tools include mechanical jack and wheel wrench.

- Undercoating on body rocker panels, step panels and wheel housings.
- **Bright body side moldings w/black trim.**
- **Bright wheel opening moldings.**
- Glass includes windshield, front side doors, rear doors, side load door and LH front quarter flip-out glass, and RH and LH rear quarter fixed glass.

INTERIOR

- RH and LH side door and rear seat padded armrests. Door trim panels are **embossed, color-keyed vinyl on door and sidewalls coordinated with seat trim and carpeting on lower areas. Also, color-keyed plastic trim panels to conceal rear seat armrest supports and seat risers.**
- Five passenger seating with front adjustable high-back bucket seats and removable 3-passenger bench seat with **the choice of custom vinyl or custom cloth seat trim.** (G30/3500 models w/7400 lb.

- **Embossed, black rubber stepwell mats for top surface of front and rear door stepwells.**
- Latex foam rubber door seals.
- **Front dome and reading lamp** and rear dome lamp with front door-actuated switches.
- Floor-covering consists of **color-keyed carpeting over entire floor area.**
- RH and LH padded, color-keyed sunshades. **RH visor mirror.**
- Gages include speedometer, odometer, fuel level, voltmeter, oil pressure, engine temperature and

- **Full-length cloth headliner is color-keyed to seat trim color.**
- Parcel tray on top surface of instrument panel extension, includes beverage holder provisions.
- Spare tire carrier on RH rear side.
- Spare tire cover.
- Insulation and sound-deadening material under instrument panel, front floor panel, engine cover front extension, inside engine cover, **above headliner and on wheelhousing areas.**
- **Full garnish moldings.**
- **Cigarette lighter.**

MODEL	TRANSMISSION	AXLES				POWER →	
		← ECONOMY	3.08	3.42	3.73	4.10	
G11006/ZW9	MAN 4-SPD	MAN 4-SPD	AUTO 4-SPD				
ENGINE							
4.3L V6 (LB4)	S	—	—	—	S ¹	—	5600
STANDARD					O ²	—	6000
5.0L V8 (L03)	—	—	—	S	—	—	5600
OPTIONAL				O	—	—	6000

¹ N/A C60 AIR CONDITIONING ² REQUIRES KC4 ENGINE OIL COOLER

MODEL	TRANSMISSION	AXLES				POWER →	
		← ECONOMY	3.08	3.42	3.73	4.10	
G10 SPORTVAN/RALLY (125-IN. WB)	MAN 4-SPD	MAN 4-SPD	AUTO 4-SPD				
G11306/ZW9							
G10 BEAUVILLE/RALLY STX (125-IN. WB) G11306/E94							
ENGINE							
4.3L V6 (LB4)	S	—	—	—	S ¹	—	5600
				S	O ²	—	6000
5.0L V8 (L03) ¹	—	—	S	O	—	—	5600
5.7L V8 (L05) ¹	—	—	S	O	—	—	6000

¹ N/A C60 AIR CONDITIONING ² REQUIRES KC4 ENGINE OIL COOLER ³ REQUIRES P215/75R15 TIRES

MODEL	TRANSMISSION	AXLES				POWER →	
		← ECONOMY	3.08	3.42	3.73	4.10	
G20 SPORTVAN/RALLY G21306/ZW9	MAN 4-SPD	MAN 4-SPD	AUTO 4-SPD				
G20 BEAUVILLE/RALLY STX G21306/E94							
ENGINE							
4.3L V6 (LB4)	S	—	—	—	S ¹	—	6600
5.0L V8 (L03)	—	—	—	S	O ²	—	6600
5.7L V8 (L05)	—	—	S	O	O ³	—	6600
6.2L V8 DIESEL (1113)	S	—	—	S	—	—	6650

¹ N/A C60 AIR CONDITIONING OR G80 LOCKING DIFFERENTIAL ² N/A G80 LOCKING DIFFERENTIAL. REQUIRES KC4 ENGINE OIL COOLER
³ REQUIRES Z82 TRAILERING, N/A G80 LOCKING DIFFERENTIAL ⁴ STANDARD W/HIGH ALTITUDE EMISSIONS

MODEL	TRANSMISSION	AXLES				POWER →	
		← ECONOMY	3.08	3.23	3.73	4.10	
G30 SPORTVAN/RALLY G31306/ZW9	MAN 4-SPD	MAN 4-SPD	AUTO 4-SPD				
G30 BEAUVILLE/RALLY STX G31306/E94							
ENGINE							
5.7L V8 (L05) ¹	—	—	—	S	—	—	7400

31306/ZW8/C6P	MAN 4-SPD	MAN 5-SPD	AUTO 3-SPD	AUTO 4-SPD	3.08	3.23	3.73	4.10	
G30 BEAUVILLE/RALLY									
31306/E94/C6P									
ENGINE									
5.7L V8 (L05)	—	—	S	—	—	—	S	O	8600
6.2L V8 DIESEL (L14)	—	—	S	—	—	—	S	O	8600

HORSEPOWER AND TORQUE RATINGS (G SPORTVAN/RALLY)									
ENGINES									
ORDERING CODE	4.3L V6	5.0L V8	5.7L V8	6.2L V8 DIESEL	6.2L V8 H.D. DIESEL				
	LB4	L03	L05	LH6	L14				
			UP TO 8600 LBS. GVWR	UP TO 8600 LBS. GVWR	8600 LBS. GVWR				
SAE NET HORSEPOWER @ RPM	150 @ 4000	170 @ 4000	195 @ 4000	130 @ 3600	148 @ 3600				
SAE NET TORQUE LB. FT. @ RPM	230 @ 2400	255 @ 2400	290 @ 2400	240 @ 2000	259 @ 2000				
FUEL SYSTEM	EFI	EFI	EFI	GEAR DRIVEN MECHANICAL FUEL INJECTION	GEAR DRIVEN MECHANICAL FUEL INJECTION				
CLUTCH SIZE (IN.)	11	11	—	12	—				
STD. Battery (Cold Cranking Amps @ 0°F)	525	525	525	2 @ 540 Each	2 @ 540 Each				

Total available for people, cargo, and equipment.

MODEL NUMBER	GAS 110-IN WB		GAS 11006/ ZW9	GAS 11306/ ZW9	GAS 11306/E94	GAS 11306/ZW9		GAS 11306/E94	GAS 11306/ZW9/C6P		GAS 11306/E94/C6P
	GAS 110-IN WB	GAS 11306/ ZW9				GAS 11306/E94	GAS 11306/ZW9		GAS 11306/E94	GAS 11306/ZW9/C6P	
SUSPENSION (OPT)											
Option	J55		J55	G50	G50	G50	C6P		C6P		
Maximum Available Payload (lbs.) ¹	1915		1760	1624	2354	2106	2218	1970	3865	3545	3409
Total GVWR (lbs.)	6000			6000	6600	6850	6600	6850	8600		
FRONT: GAWR (lbs.)	3166			3166	3400	3670	3400	3670	3900		
REAR: GAWR (lbs.)	3166			3166	3400	3400	3400	3400	5360		
FRONT: Suspension Type	Ind. Coil Spring			Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring	Ind. Coil Spring		
Standard Spring Capacity (lbs.)	3400			3400	3400	3670	3400	3670	3900		
REAR: Suspension Type	Semi-Elliptic 2-Stage Multi-Leaf			Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf	Semi-Elliptic 2-Stage Multi-Leaf		
Standard Spring Capacity (lbs.)	3400			3400	3400	3400	3400	3400	5400		
Leaves Per Spring	5			5	5	5	5	5	8		
Leaf Total Thickness (in.)	1.97			1.97	2.03	2.03	2.03	2.03	3.00		
FRONT: Shock Absorber Piston Diameter (mm) STD/OPT	32			32	32	32	32	32	32		
Stabilizer Bar Diameter (in.) STD/OPT	—/1.06			—/1.06	—/1.06	—/1.06	—/1.06	—/1.06	1.06/—		
REAR: Shock Absorber Piston Diameter (mm) STD/OPT	32			32	32	32	32	32	32		
FRONT: Axle Type	—			—	—	—	—	—	—		
Make	—			—	—	—	—	—	—		
Maximum Capacity (lbs.)	3400			3400	3400	3675	3400	3675	3900		
REAR: Axle Type	Semi-Floating			Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating		
Make	GM			GM	GM	GM	GM	GM	—		
Maximum Capacity (lbs.)	3500			3500	3500	3500	3500	3500	5700		
Pinion/Ring Gear Type	Hypoid			Hypoid	Hypoid	Hypoid	Hypoid	Hypoid	Hypoid		
Standard Tires	Front/ Rear	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless SBR P215/75R15	Tubeless Nylon Bias 8.75-16.5-E	Tubeless Nylon Bias 8.75-16.5-E	Tubeless Nylon Bias 8.75-16.5-E
Tire Capacity (lbs. each)		1583	1583	1703	1843	1703	1703	1843	1990/2680		
Inflation (PSI)		35	35	35	35	35	35	35	75		
Wheel Size (in.)		15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	15 x 6.00JJ	16.5 x 6.75		
Wheel Capacity (lbs. each)		1583	1583	1583	1583	1583	1583	1583	2680		
Bolt Holes		5	5	5	5	5	5	5	8		
Bolt Circle Diameter (in.)		5	5	5	5	5	5	5	6.5		
Offset (mm)		9	9	9	9	9	9	9	34		
Revolutions per mile @ 45 MPH		753	753	753	753	753	753	753	712		

¹Total available for people, cargo, and equipment.

MODEL NUMBER	G11006/ZW9-G11306/ZW9-G11306/E94	G21306/ZW9-G21306/E94	G31306/ZW9-G31306/E94	G31306/ZW9/C6P-G31306/E94/C6P
STEERING				
Type	Integral Power	Integral Power	Integral Power	Integral Power
Steering Ratio	17.2:1	17.2:1	17.2:1	17.2:1
Turning Diameter: Curb-To-Curb (ft.) Wall-To-Wall (ft.)	41.3/45.9 42.7/46.2	46.0 47.5	48.5 49.8	48.5 49.8

MODEL	G10/1500 SPORTVAN/ RALLY-BEAUUVILLE/ RALLY STX	G20/2500 SPORTVAN/ RALLY-BEAUUVILLE/ RALLY STX	G30/3500 SPORTVAN/ RALLY-BEAUUVILLE/ RALLY STX	G30/3500 SPORTVAN/RALLY- BEAUUVILLE/RALLY STX
MODEL NUMBER	G11006/ZW9-G11306/ZW9-G11306/E94	G21306/ZW9-G21306/E94	G31306/ZW9-G31306/E94	G31306/ZW9/C6P-G31306/E94/C6P
	J50 J55	B3J		B3J
BRAKES				
GVWR	5600	6000	6600	6850
Type	Vac. Power Front Disc/ Rear Drum	Vac. Power Front Disc/ Rear Drum	Vac. Power Front Disc/ Rear Drum	Vac. Power Front Disc/ Rear Drum
Booster (Diaphragm Diameter) (in.)	9.5 Single	9.5 x 8.0 Tandem	9.5 x 8.0 Tandem	9.5 x 8.0 Tandem
Front Rotor Size (Diameter x Thickness) (in.)	11.86 x 1.29	11.86 x 1.29	12.50 x 1.28	12.50 x 1.28
Front Facing Contact Per Axle (sq. in.)	37.63	37.63	42.98	42.98
Rear Drum Size (Diameter x Width) (in.)	11.0 x 2.0	11.15 x 2.75	11.15 x 2.75	13.0 x 2.5
Rear Facing Contact Per Axle (sq. in.)	74.34	107.42	107.42	116.73
Parking Brake	Cable To Rear Wheels	Cable To Rear Wheels	Cable To Rear Wheels	Cable To Rear Wheels

MODEL	G10/G1500 SPORTVAN/ RALLY-BEAUUVILLE/ RALLY STX				G20/G2500 SPORTVAN/ RALLY-BEAUUVILLE/ RALLY STX				G30/3500 SPORTVAN/RALLY- BEAUUVILLE/ RALLY STX	
MODEL NUMBER	G11006/ZW9-G11306/ZW9- G11306/E94				G21306/ZW9-G21306/E94				G31306/ZW9- G31306/E94	
STANDARD COOLING SYSTEM										
Engine	4.3L V6	5.0L V8	5.7L V8	5.7L V8	4.3L V6	5.0L V8	5.7L V8	6.2L V8	5.7L V8	6.2L V8
Standard Radiator Thickness (in.)	.93	.98	.98	.98	.93	.98	.98	1.57	.98	1.57
Total System Cap. (gal.)	3.4	4.2	4.2	4.2	3.4	4.2	4.2	6.3	5.8	6.2
Standard Fan (No. Blades x Diameter x Pitch)	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	5 x 20 x 2.87	5 x 19.5 x 2.0	5 x 20 x 2.87
OPTIONAL COOLING SYSTEMS										
Engine	4.3L V6	5.0L V8	5.7L V8	5.7L V8	4.3L V6	5.0L V8	5.7L V8	6.2L V8	5.7L V8	6.2L V8
AUTOMATIC TRANS.	MX0	MX0	MX0	MX0	MX0	MX0	MX0	MX0	MX0	MX1
Radiator Thickness (in.)	.93	.98	.98	.98	.93	.98	.98	1.57	.98	1.57
Total Systems Cap. (gal.)	3.4	4.2	4.2	4.2	3.4	4.2	4.2	6.2	4.5	6.2
Fan (No. Blades x Diameter x Pitch)	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	3 x 19 x 2.0	5 x 20 x 2.87	5 x 19.5 x 2.0	5 x 20 x 2.87
OPT. AIR CONDITIONING	C60 ¹	C60 ¹	C60 ¹	C60 ¹	C60 ¹	C60 ¹	C60 ¹	C60 ¹	C60	C60
Radiator Thickness (in.)	.93	.98	1.57	1.57	.93	.98	1.57	1.57	1.57	2.17
Total System Cap. (gal.)	3.3	4.2	4.2	4.2	3.3	4.2	4.2	6.2	4.2	6.2
Fan (No. Blades x Diameter x Pitch)	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 20 x 2.87	5 x 19.5 x 2.0	5 x 20 x 2.87
OPT. H.D. RADIATOR AND TRANS. OIL COOLER	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²	V02 ²
Radiator Thickness (in.)	1.34	1.57	1.57	1.57	1.57	1.57	1.57	1.57	1.57	2.17
Total System Cap. (gal.)	3.4	4.2	4.2	4.2	3.4	4.5	4.5	6.2	4.5	6.2
Fan (No. Blades x Diameter x Pitch)	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 19.5 x 2.0	5 x 20 x 2.87	5 x 19.5 x 2.0	5 x 20 x 2.87

¹N/A LB4 Engine and MM7 Transmission.

²Reqs. MX0 Trans. and V05 Cooling. C60, or C69 air (LB4 Eng. Reqs. KC4 cooler) include w/Z28 Trailering on G-20/2500 and G30/3500 models.

[illegible]

calculating payload capacity, gross
axle weight, axle reserve capacity,
gross vehicle weight and total
reserve capacity.

For more information on
calculating these capacities, consult
the "FORMS" section of this book.

MODEL WEIGHTS			
MODEL/BODY	WEIGHT (lbs.)		
	FRONT	REAR	TOTAL
G11006/ZW9	2641	2185	4826
G11306/ZW9	2763	2217	4980
G11306/E94	2817	2315	5132
G21306/ZW9	2785	2224	5009
G21306/ZW9/B3J	3198	2294	5492
G21306/E94	2845	2329	5174
G21306/E94/B3J	3318	2440	5758
G31306/ZW9/C6C	3052	2663	5715
G31306/ZW9/C6P	3100	2762	5862
G31306/ZW9/C6P/B3J	3040	2515	5555
G31306/E94/C6C	3340	2536	5876
G31306/E94/ZW9/C6P	3088	2613	5701
G31306/E94/C6P/B3J	3441	2693	6134

CURB WEIGHTS			
MODEL/BODY	WEIGHT (lbs.)		
	FRONT	REAR	TOTAL
G11006/ZW9	2255	1821	4076
G11306/ZW9	2330	1900	4230
G11306/E94	2384	1998	4382
G21306/ZW9	2352	1907	4259
G21306/ZW9/B3J	2765	1977	4742
G21306/E94	2412	2012	4424
G21306/E94/B3J	2885	2123	5008
G31306/ZW9/C6C	2619	2346	4965
G31306/ZW9/C6P	2667	2445	5112
G31306/ZW9/C6P/B3J	2607	2198	4805
G31306/E94/C6C	2907	2219	5126
G31306/E94/ZW9/C6P	2655	2296	4951
G31306/E94/C6P/B3J	3008	2376	5384

***4	0	0
***6	12	5

PAINT WEIGHTS			
CODE	CONDITION	WEIGHT (lbs.)	
		FRONT	REAR
ZY1		0	0
ZY3	w/o E94	5	8
	w/E/94	0	0
ZY4	w/o E94	5	8
	w/E94	0	0
ZY5	w/o E/94	6	9
	w/E94	0	0

—A—	AA3	0	0
	AD8	0	2
	AJ1	0	0
	AQ3	116	434
	AQ4	0	0
	w/o C6P	73	1218
	w/C6P	6	1
—B—	AU3	0	0
	A01	0	0
	A02	0	0
	A18	0	1
	A31	7	2
	BA8	2	1
	B30	9	11
	B32	4	0
	B33	5	3
	B6S	19	23
	G10	19	23
	G20-30	19	23
	w/o AQ3	8	38
	w/AQ3	4	8
		1	1
—C—	CD4	1	0
	C36	12	10
	G11306-21306-31306	11	12
	G11006	56	-6
	w/LB4	55	-5
	G11006		
	G11306-21306		
	w/o		
	LB4/LH6/LL4	54	-4
	w/LH6	80	-3
	w/LL4	87	-4
	w/LB4	59	36
	G11006		
	G11306-21306	58	38
	w/o LB4/LH6/LL4	89	37
—D—	w/LH6	82	38
	w/LL4	57	39
	D45	5	0
	D85	0	0
—E—	E24	-1	-1
	G11006		
	G11306-21306-		

F59	—F—	21	02	NA5	—N—	0	0	YCE	—Y—	0	0
	—G—			NA6		0	0	YCU		0	6
GQ1		0	0	NK3		-2	0	YCV		0	6
GT4		0	0	NL7	w/o LH6/LL4	-19	107	YCW		0	5
GT5		0	0		w/LH6/LL4	-23	131	YET		0	0
GU5		0	0	N31		1	0	YEU		0	0
GU6		0	0	N33		4	0	YEV		0	0
G50	G10	0	0	N67	G10	12	17	YF5		0	0
	G20	0	0		G20	2	3	YRU		0	3
G80		0	3		—P—			YSD		0	5
		0	7	PA1		2	2	YTH		0	0
J55	—J—	2	10		—T—			YVD	—Z—	0	14
KC4	—K—	6	-1	TR9		1	1	ZCE		0	0
K05		1	0	TT5		3	0	ZCU		0	3
				TVR		1	1	ZCV		0	3
LB4	—L—	0	0	UA1	—U—			ZCW		0	3
L03	G11306-21306	146	-4	UM6	w/o LB4	5	0	ZET		-5	32
LH6	G11006	149	-4	UM7	w/LB4	4	0	ZEU		-5	32
LL4		0	0	UU9		10	3	ZEV		-5	32
L05	G10-20	125	11	UX1		4	0	ZQ2		13	2
	G30	0	0	U35		2	0	ZQ3		10	0
				U37		4	0	ZRU		-8	50
	—M—			U63		0	0	ZSD		-12	85
MX0	G11006 w/LB4	17	19	U66	—V—	5	1	ZTH		-8	48
	w/o YF5	28	19			1	3	ZVD		-9	56
	w/LB4 w/YF5	14	22	V02		6	-1	Z72	G21306	-5	28
	w/L03			V05	w/o MX0				w/o LH6	21	79
	G11306 w/LB4	19	17	V31	w/MX0	6	-1		G31306	4	81
	w/o YF5	30	17	V37		3	-1		w/o LL4	0	79
	w/LB4 w/YF5	16	19		—X—	11	-3		w/LL4	-17	81
	w/L03	-4	-6			0	0				
	w/L05	30	18	XCE							
	G21306 w/LB4	16	20	XCU		0	0				
	w/L03	-12	5	XCV		6	0				
	w/LH6	4	5	XCW		5	0				
	w/L05	-6	-3	XET		0	0				
	G31306 w/L05	-14	-2	XEU		0	0				
	w/LL4	0	0	XEV		0	0				
MX1	G30			XRU		3	0				
				XSD		3	0				
				XTH		0	0				
				XVD		14	0				

