



ASTRO PASSENGER VAN

ASTRO PASSENGER VAN





CONTENTS



	<u>Page</u>
MODELS	2
ASTRO CS TRIM	3
ASTRO CL (YC6) TRIM	4
ASTRO LT (YC7) TRIM	5
POWERTRAINS	6
STANDARD SUSPENSION	8
WHEELS AND TIRES/STEERING AND BRAKES	9
ELECTRICAL/COOLING	10
DIMENSIONS	11
OPTIONS	12
COLOR COMBINATIONS	14
EXTERIOR COLORS	B
INTERIOR TRIM	C
SEATS	D
TRAILERING	E

ASTRO PASSENGER VAN

TWO-WHEEL DRIVE PASSENGER VAN

ASTRO PASSENGER VAN	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX ¹ PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	ASTRO PASSENGER VAN
	CM10906	111	5700	1791	5/7/8	4.3L V6/A4	4.3L HP V6/A4 (L35)	The standard Astro Passenger Van model is offered in a 5700-lb. GVWR with a choice of seating configurations.
ASTRO EXTENDED PASSENGER VAN	CM11006	111	5950	1957	5/7/8	4.3L V6/A4	4.3L HP V6/A4 (L35)	ASTRO EXTENDED PASSENGER VAN The Astro Extended Passenger Van retains the same 111-in. wheelbase as the regular-length model, while adding 10-inches to the rear frame for increased cargo capacity.
								

ALL-WHEEL DRIVE PASSENGER VAN

ASTRO ALL-WHEEL DRIVE PASSENGER VAN	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX ¹ PAYLOAD (LBS.)	PASS. CAP. STD/OPT	STD ENGINE/TRANS	OPT ENGINE/TRANS	ASTRO ALL-WHEEL DRIVE PASSENGER VAN
	CL10906	111	5950	1768	5/7/8	4.3L HP V6/A4	—	The Astro All-Wheel Drive Passenger Van offers a 5950 GVWR with full-time All-Wheel Drive.
ASTRO ALL-WHEEL DRIVE EXTENDED PASSENGER VAN	CL11006	111	6100	1841	5/7/8	4.3L HP V6/A4	—	ASTRO ALL-WHEEL DRIVE EXTENDED PASSENGER VAN The Astro All-Wheel Drive Extended Passenger Van retains the same 111-in. wheelbase as the regular-length model, while adding 10-inches to the rear frame for increased cargo capacity.
								

¹Based on curb weight

ASTRO PASSENGER VAN SEATING ARRANGEMENTS


STANDARD: 5-PASSENGER (ZP5)

Includes high-back front bucket seats and a standard removable 3-passenger bench seat. With YC7 trim, includes reclining front bucket seats and a removable split-back reclining 3-passenger bench seat with folding armrests.




OPTIONAL: 7-PASSENGER (RPO ZP7)

Includes four high-back bucket seats and a removable 3-passenger bench seat. Also includes A78 reclining seat backs on bucket seats. With YC7 trim, includes four reclining bucket seats (2 front and 2 center), and a removable split-back reclining 3-passenger bench seat with folding armrests.




OPTIONAL: 8-PASSENGER (RPO ZP8)

Includes two high-back buckets and two removable 3-passenger bench seats. With YC7 trim, includes two reclining bucket seats and two removable split-back reclining 3-passenger bench seats with folding armrests.





ASTRO PASSENGER VAN WINDOW AND DOOR ARRANGEMENTS

STANDARD
(Includes Rear Door Windows, Side Sliding Door Window and LH Center Window)





W/ZW6
(Includes RH and LH Rear Quarter Windows)



NOTE: Right face profile is identical to left face profile.

W/ E54
Rear door, split panels



ASTRO CS

(ZW9)

The CS trim level is the standard trim level of the Astro series. It is designed to offer buyers a high level of standard features when purchasing a standard-level vehicle.

The following features are standard.

POWERTRAIN/CHASSIS

- ALTERNATOR: 100 Amp Delcotron.
- BATTERY: 12 volt, neg. ground; 630 CCA @ 0 degrees F.
- BRAKES: Power; vacuum (CM10906 only). Front—disc. Rear—drum. Power; hydraulic (CM11006, CL10906 and CL11006). Front—disc. Rear—drum. Includes four-wheel anti-lock braking system.
- ENGINE: 4.3-liter Vortec V6 engine with Electronic Fuel Injection (EFI) on 2-wheel drive. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm. 4.3-liter Vortec High Performance V6 engine with Central Port Injection

on All-Wheel Drive. It produces 200 net horsepower @ 4400 rpm and 260 lb-ft of net torque @ 3600 rpm.

- EXHAUST: Single.
- FRAME: Integral body design with boxed section front stub frame.
- FUEL TANK: 27.0-gallon (approx.).
- REAR AXLE: Hypoid, Semi-Floating. Ratio: 3.23 on CM10906 and CM11006. 3.42 on CL10906 and CL11006.
- SHOCK ABSORBERS: Front and Rear. 32 mm piston dia.

- STABILIZER BAR: Front. 1.26 inch dia. on CM10906 and CM11006. 1.18 inch dia. on CL 10906 and CL11006.
- STEERING: Integral Power Variable Ratio—16/13:1.
- SUSPENSION: Front—Independent with computer-selected springs. Rear—wheel drives with coil springs; all-wheel drives with torsion bars. Rear—Composite leaf springs.
- TRANSFER CASE: CL10906 and CL11006 models.
- TRANSMISSION: 4-Speed automatic with overdrive.

EXTERIOR

- AIR DAM: Black.
- BUMPER: Front and rear painted lower body color, with front bumper guards on all models.
- COLORS: Choice of ten in a solid paint scheme. See Color and Trim specifications for details.
- CORROSION PROTECTION: Underbody.
- DOORS: Driver and passenger front side, sliding RH side cargo, and RH and LH rear load doors.

- GLASS: Windshield, front side doors, RH/LH front quarter windows and fixed glass on rear doors.
- GRILLE: Black molded plastic.
- HEADLAMPS: Single halogen.
- HORN: Dual high-note and low-note.
- LICENSE PLATE BRACKET: Front and rear.
- MIRRORS: Black RH and LH fixed with pivoting arm and adjustable heads. Head size is 4 $\frac{3}{4}$ " x 7".

- SPARE TIRE/WHEEL: Compact; mounted under floor.
- TIRES: Four all-season steel belted radials. P205/75R15 on CM10906 and P215/75R15 on CL10906, CL11006 and CM11006.
- WHEELS: Four 15.0" x 6.0" argent steel wheels. Includes bright metal hub caps with black trim.
- WINDOW PILLARS: Black.

INTERIOR

- ARMREST: RH and LH front door.
- ASSIST HANDLES: RH passenger and sliding door pillar.
- BEVERAGE HOLDERS: Two located on top of the engine cover panel.
- CHIMES: Headlamp warning.
- CIGARETTE LIGHTER: Includes ashtray light located in engine cover panel.
- COAT HOOKS: Two LH and one RH.
- COLORS: Choice of Blue, Garnet, Beige or Gray.
- DOME LAMP: Two with front door actuated switches.
- DOOR PANELS: Color-keyed vinyl with front door map pockets.
- DOOR SILL PLATE: Black plastic.
- FLOOR COVERING: Color-keyed carpeting on wheelhouses and entire floor.

- FUEL FILLER DOOR: Remote release, front upper corner driver side stepwell.
- GAUGES: Includes speedometer, odometer, trip odometer, fuel level, voltmeter, oil pressure, coolant temperature, and additional telltale lights.
- HEADLINER: Full length, color-keyed, foam backed cloth.
- HEATER: Deluxe with windshield and side window defoggers.
- MIRRORS: 10 inch rearview.
- RADIO: Electronically-tuned AM with two 6" diameter front dash speakers and fixed mast antenna. (Refer to Delco Electronics brochure in RPO Detail for further information.)
- SEATS: Front high-back adjustable buckets with custom trim plus removable center fore/aft adjustable 3-passenger bench; includes seat adjuster.


- STEERING WHEEL: Black custom 4-spoke.
- STORAGE COMPARTMENT: Molded, color-keyed plastic in LH rear quarter area.
- STOWAGE BOX: Located in front face of engine cover extension.
- SUNSHADES: Color-keyed RH and LH padded cloth with RH visor mirror.
- SWING-OUT GLASS: Included on sliding side door.
- TOOLS: Screw-operated scissor-type jack with ratchet handle and extension and two wheel blocks. Located behind side panel at right rear.
- WINDOWS: Tinted glass; swing-out glass on LH body front and sliding side door.
- WINDSHIELD WIPERS: Intermittent.

ASTRO CL

(YC6)

The CL trim level is an optional trim level for the Astro series. It is designed to offer buyers an increased level of comfort and convenience features compared to the standard CS trim.

The following features are standard. Bold type denotes equipment in addition to or replacing that of the CS trim.



Some equipment shown may be optional or extra cost.

POWERTRAIN/CHASSIS

- 1 ALTERNATOR: 100 Amp Delcotron.
- 1 BATTERY: 12 volt, neg. ground; 630 CCA @ 0 degrees F.
- 1 BRAKES: Power; vacuum (CM11006, CM10906 only). Front—disc. Rear—drum. Power; hydraulic (CL10906 and CL11006). Front—disc. Rear—drum. Includes four-wheel anti-lock braking system.
- 1 ENGINE: 4.3-liter Vortec V6 engine with Electronic Fuel Injection (EFI) on 2-wheel drive. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm. 4.3-liter Vortec High Performance V6 engine with Central Port Injection on All-Wheel Drive. It produces 200 net horsepower @ 4400 rpm and 260 lb-ft of net torque @ 3600 rpm.
- 1 EXHAUST: Single.
- 1 FRAME: Integral body design with boxed section front stub frame.
- 1 FUEL TANK: 27.0-gallon (approx.).
- 1 REAR AXLE: Hypoid, Semi-Floating. Ratio: 3.23 on CM10906 and CM11006. 3.42 on CL10906 and CL11006.
- 1 SHOCK ABSORBERS: Front and Rear. 32 mm piston dia.
- 1 STABILIZER BAR: Front. 1.26 inch dia. on CM10906 and CM11006. 1.18 inch dia. on CL10906 and CL11006.
- 1 STEERING: Integral Power Variable Ratio—16/13:1.
- 1 SUSPENSION: Front—Independent with computer-selected springs. Rear—wheel drives with coil springs; all-wheel drives with torsion bars. Rear—Composite leaf springs.
- 1 TRANSFER CASE: CL10906 and CL11006 models.
- 1 TRANSMISSION: 4-Speed automatic with overdrive.

EXTERIOR

- 1 AIR DAM: Includes fog lamps.
- 1 BUMPER: Front and rear lower body color with matching color-keyed end caps, black rub strips with bright trim and rear black combination top step surface. Includes front bumper guards.
- 1 COLORS: Choice of ten in a solid paint scheme. See Color and Trim specifications for details.
- 1 CORROSION PROTECTION: Underbody.
- 1 DOORS: Driver and passenger front side, sliding RH side cargo and RH and LH rear load doors.
- 1 GRILLE: Black molded plastic with argent paint on feature surfaces.
- 1 HEADLAMPS: Single halogen.
- 1 HORN: Dual high-note and low-note.
- 1 LICENSE PLATE BRACKET: Front and rear.
- 1 MIRRORS: Black RH and LH fixed with pivoting arm and adjustable heads. Head size is 4³/₄" x 7".
- 1 MOLDINGS: Black body side with bright trim.
- 1 SPARE TIRE/WHEEL: Compact; mounted under floor.
- 1 TIRES: Four all-season steel belted radials. P205/75R15 on CM10906 and P215/75R15 on CL10906, CL11006 and CM11006.
- 1 WHEEL OPENING MOLDINGS: Black.
- 1 WHEELS: Four 15.0" x 6.5" color-keyed steel rally wheels. Bright trim rings with black center cap.
- 1 WINDOW PILLARS: Black.

INTERIOR

- 1 ARMREST: RH and LH front door.
- 1 ASSIST HANDLES: RH passenger and sliding door pillar.
- 1 BEVERAGE HOLDERS: Two located on top of the engine cover panel.
- 1 CHIMES: Headlamp warning.
- 1 CIGARETTE LIGHTER: Includes ashtray light. Included in engine cover panel.
- 1 COAT HOOKS: Two LH and one RH.
- 1 COLORS: Choice of Blue, Garnet, Beige or Gray.
- 1 DOME LAMP: Two with front door, rear door and sliding door-actuated switches. Includes door-jamb override switch.
- 1 DOOR PANELS: Color-keyed expanded vinyl with carpet inserts, insulation and front door map pockets.
- 1 DOOR SILL PLATE: Black plastic.
- 1 FLOOR COVERING: Color-keyed carpeting on wheelhouses and floor.
- 1 FLOOR MATS: Front and rear color-keyed.
- 1 FUEL FILLER DOOR: Remote release; front upper corner driver side stepwell.
- 1 GAUGES: Includes speedometer, odometer, trip odometer, fuel level, voltmeter, oil pressure, coolant temperature and additional telltale lights.
- 1 HEADLINER: Full length, color-keyed, foam backed cloth.
- 1 HEATER: Deluxe with windshield and side window defoggers.
- 1 LAMPS: Stepwell and stowage box.
- 1 MIRRORS: 10 inch rearview.
- 1 RADIO: Electronically-tuned AM with two 6" diameter front dash speakers and fixed mast antenna. (Refer to Delco Electronics brochure in RPO Detail for further information.)
- 1 SEATS: Front high-back adjustable buckets with all-vinyl trim plus removable center fore/aft adjustable 3-passenger bench which includes seat adjuster. Choice of Custom Vinyl or Custom Cloth with Vinyl trim.
- 1 STEERING WHEEL: Black Custom 4-spoke.
- 1 STORAGE COMPARTMENT: Molded, color-keyed plastic in LH rear quarter area.
- 1 STOWAGE BOX: Located in front face of engine cover extension. Includes beverage holder.
- 1 SUNSHADES: Color-keyed RH and LH padded cloth with RH visor mirror with light.
- 1 SWING-OUT GLASS: Included on sliding side door and rear door.
- 1 TOOLS: Screw-operated scissor-type jack with ratchet handle and extension and two wheel blocks. Located behind side panel at right rear.
- 1 WINDOWS: Tinted glass.
- 1 WINDSHIELD WIPERS: Intermittent.

ASTRO LT

(YC7)

The LT trim level is an optional trim level for the Astro series. It is designed to offer buyers an increased level of comfort and convenience features compared to the standard CS trim and the optional CL trim.

The following features are standard. Bold type denotes equipment in addition to or replacing that of the CL trim.

POWERTRAIN/CHASSIS

- ALTERNATOR: 100-Amp Delcotron.
- BATTERY: 12 volt, neg. ground; 630 CCA @ 0 degrees F.
- BRAKES: Power; vacuum (CM10906 and CM11006). Front-disc. Rear-drum. Power; hydraulic (CL10906 and CL11006). Front-disc. Rear-drum. Includes four-wheel anti-lock braking system.
- ENGINE: 4.3-liter Vortec V6 engine with Electronic Fuel Injection (EFI) on 2-wheel drive. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm. 4.3-liter Vortec High

Performance V6 engine with Central Port Injection on All-Wheel Drive. It produces 200 net horsepower @ 4400 rpm and 260 lb-ft of net torque @ 3600 rpm.

- EXHAUST: Single.
- FRAME: Integral body design with boxed section front stub frame.
- FUEL TANK: 27.0 gallon (approx.).
- REAR AXLE: Hypoid, Semi-Floating. Ratio: 3.23 on CM10906 and CM11006. 3.42 on CL10906 and CL11006.
- SHOCK ABSORBERS: Front and Rear. 32 mm piston dia.

- STABILIZER BAR: Front. 1.26 inch dia. on CM10906 and CM11006. 1.18 inch dia. on CL10906 and CL11006.
- STEERING: Integral Power Variable Ratio-16/13:1.
- SUSPENSION: Front-Independent with computer-selected springs. Rear-wheel drives with coil springs; all-wheel drives with torsion bars. Rear-Composite leaf springs.
- TRANSFER CASE: CL10906 and CL11006 models.
- TRANSMISSION: 4-Speed automatic with overdrive.

EXTERIOR

- AIR DAM: Includes fog lamps.
- BUMPER: Front and rear lower body color with matching color-keyed end caps, black rub strips with bright trim and rear black combination top step surface. Includes front bumper guards.
- COLORS: Choice of **three** in a solid paint scheme. See Color and Trim specifications for details.
- CORROSION PROTECTION: Underbody.
- DOORS: Driver and passenger front side, sliding RH side cargo and RH and LH rear load doors.

- GRILLE: Black molded plastic with argent paint on feature surfaces.
- HEADLAMPS: Single halogen.
- HORN: Dual high-note and low-note.
- LICENSE PLATE BRACKET: Front and rear.
- MIRRORS: Black RH and LH fixed type with pivoting arm and adjustable heads. Head size is 4³/₄" x 7.0".
- MOLDINGS: Black body side with bright trim.

- SPARE TIRE/WHEEL: Compact; mounted under floor.
- STRIPING: **Wide, color-keyed, at beltline.**
- TIRES: Four all-season steel belted radials. P205/75R15 on CM10906 and P215/75R15 on CL10906, CM11006 and CL11006.
- WHEEL OPENING MOLDINGS: Black.
- WHEELS: Four 15.0" x 6.5" steel rally wheels. **Color-keyed to body color.**
- WINDOW PILLARS: Black.

INTERIOR

- ARMREST: RH and LH front door.
- ASSIST HANDLES: RH passenger and sliding door panels.
- BEVERAGE HOLDERS: Two located on top of engine cover panel.
- CHIMES: Headlamp warning.
- CIGARETTE LIGHTER: Includes ashtray light. Included in engine cover panel.
- COAT HOOKS: Two LH and one RH.
- COLORS: Choice of two: Blue or Beige.
- DOME LAMP: Two with front door, rear door and sliding door-actuated switches. Includes door-jamb override switch.
- DOOR PANELS: Color-keyed expanded vinyl with carpet inserts, insulation and front-door map pockets.
- DOOR SILL PLATE: **Color-keyed including scuffplates.**
- FLOOR COVERING: Color-keyed carpeting on wheelhouses and floor.
- FLOOR MATS: Front and rear color-keyed.



- FUEL FILLER DOOR: Remote release; front upper corner driver side stepwell.
- GAUGES: Includes speedometer, odometer, trip odometer, fuel level, voltmeter, oil pressure, coolant temperature, and additional telltale lights.
- HEADLINER: Full length, color-keyed, foam backed cloth.
- HEATER: Deluxe with windshield and side window defoggers.
- LAMPS: Stepwell and stowage box.
- MIRRORS: 10 inch rearview.
- RADIO: Electronically-tuned AM with two 6" diameter front dash speakers and fixed mast antenna. (Refer to Delco Electronics brochure in RPO Detail for further information.)
- SEATS: **Special front buckets with reclining backs, folding armrests and full-width adjustable head restraints. Split-back center seat includes fold-down center console with convenience**

- **tray and cup pockets and seat adjustment. RH seatback folds forward for easy access to rear. All seats are trimmed with special velour fabric.**
- STEERING WHEEL: **Special luxury sport type, with anti-theft locking feature.**
- STORAGE COMPARTMENT: LH side trim panel has a storage pouch with a zipper.
- STOWAGE BOX: Located in front face of engine cover extension. Includes beverage holder.
- SUNSHADES: Color-keyed RH and LH padded cloth with RH visor mirror with light.
- SWING-OUT GLASS: Included on sliding side door and rear door.
- TOOLS: Screw-operated scissor-type jack with ratchet handle and extension and two wheel blocks. Located behind side panel at right rear.
- WINDOWS: Full Body deep tinted glass.
- WINDSHIELD WIPERS: Intermittent.

ASTRO PASSENGER VAN

HORSEPOWER AND TORQUE RATINGS

ENGINE	4.3L V6	4.3L H.P. V6
RPO CODE	LB4	L35
CHART REFERENCE CODE	A	B
SAE NET HORSEPOWER @ RPM	150 @ 4000	200 @ 4400
SAE NET TORQUE LB. FT. @ RPM	230 @ 2400	260 @ 3600
FUEL SYSTEM	EFI	CPI
CLUTCH SIZE (IN.)	—	—
STD. BATTERY (Cold Cranking Amps @ 0° F)	630	630



KEY: S - Standard
O - Optional
— Not Available

TWO-WHEEL DRIVE

MODEL	ENGINE	TRANSMISSION MX0 AUTOMATIC 4-SPEED	AXLES			GVWR
			ECONOMY	POWER	POWER	
Astro Passenger Van CM10906	4.3L V6 (LB4)	S	3.23	3.42	3.73	5700
	4.3L H.P. V6 (L35)	S	—	S	O ²	5700
Astro Extended Passenger Van CM11006	4.3L V6 (LB4)	S	S	O	O ¹	5950
	4.3L H.P. V6 (L35)	S	—	S	O ²	5950

ALL-WHEEL DRIVE

MODEL	ENGINE	TRANSMISSION MX0 AUTOMATIC 4-SPEED	AXLES		GVWR
			ECONOMY	POWER	
Astro All-Wheel Drive Passenger Van CL10906	4.3L H.P. V6 (L35)	S	3.42	3.73	5950
Astro All-Wheel Drive Extended Passenger Van CL11006	4.3L H.P. V6 (L35)	S	S	O ²	6100

¹ Requires Z82 Trailering Equipment option ² Requires V02 Cooling and KC4 Engine Oil Cooler

AUTOMATIC TRANSMISSION	
MODEL	AUTOMATIC 4-SPEED w/OVERDRIVE 4L60
RPO CODE	MX0
GEAR RATIOS	
First	3.06
Second	1.63
Third	1.00
Fourth	0.70
Reverse	2.29
GEAR TYPE	Planetary
TORQUE CONVERTER	
Element Types	Pump/Stator/Turbine
Lock-up Clutch	Automatic
LUBRICANT CAPACITY (pints)	
Dry Fill	19
Refill	10

AXLES	REAR			FRONT - ALL-WHEEL DRIVE	
MAKE AND CAPACITY (lbs.)	GM 3150 ¹			GM 3050 ¹	
PINION & RING GEARS	Hypoid			Hypoid	
Type	Hypoid			Hypoid	
Ratio	3.23	3.42	3.73	3.42	3.73
Pinion Teeth	13	12	11	12	11
Ring Gear Teeth	42	41	41	41	41
Ring Gear Dia. (in.)	7.5	7.5	7.5	7.25	7.25
DIFFERENTIAL	2-Pinion Tapered Roller			2-Pinion Tapered Roller	
Type	2-Pinion			2-Pinion	
Bearings, Type	Tapered Roller			Tapered Roller	
AXLE SHAFTS	Semi-Floating Integral Shaft and Drive Flange			—	
Type	Semi-Floating			—	
Min. Diameter (in.)	—			—	
HOUSING @ SPRING SEAT	2.69 x .116-.175			—	
Section Diameter and Thickness (in.)	2.69 x .116-.175			—	

¹Refer to Standard and Optional Suspension Pages 8 and 9 for Specific Model Availability.

		TWO-WHEEL DRIVE		ALL-WHEEL DRIVE	
MODEL	ASTRO PASSENGER VAN	ASTRO EXTENDED PASSENGER VAN	ASTRO ALL-WHEEL DRIVE PASSENGER VAN	ASTRO ALL-WHEEL DRIVE EXTENDED PASSENGER VAN	
MODEL NUMBER	CM10906	CM11006	CL10906	CL11006	
STANDARD SUSPENSION					
PAYLOAD (Maximum lbs.) ¹	1891	1757	1748	1841	
GVWR (lbs.)	5700	5950	5950	6100	
GAWR (lbs.): Front	2800	2800	3050	3050	
Rear	2900	3150	3150	3150	
FRONT SUSPENSION					
Type	Ind. Coil Spring	Ind. Coil Spring	Torsion Bar	Torsion Bar	
Standard Spring Cap. (Total lbs.)	2800	2800	3050	3050	
Front Shock Absorbers Piston Diameter (mm)	32	32	32	32	
Front Stabilizer Bar Diameter (in.)	1.26	1.26	1.18	1.18	
REAR SUSPENSION					
Type	Composite Leaf Spring	Composite Leaf Spring	Composite Leaf Spring	Composite Leaf Spring	
Standard Spring Cap. (Total lbs.)	2900	3150	3150	3150	
Leaves Per Spring	1	1	1	1	
Leaf Total Thickness (in.)	.813	.813	.813	.813	
Rear Shock Absorbers Piston Diameter (mm)	32	32	32	32	
FRONT AXLE					
Type	—	—	Independent	Independent	
Make	—	—	GM	GM	
Maximum Capacity (lbs.)	2800	2800	3050	3050	
Standard Hub Locks	—	—	Insta-Trac	Insta-Trac	
Pinion/Ring Gear Type	—	—	Hypoid	Hypoid	
REAR AXLE					
Type	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating	
Make	GM	GM	GM	GM	
Maximum Capacity (lbs.)	3150	3150	3150	3150	
Pinion/Ring Gear Type	Hypoid	Hypoid	Hypoid	Hypoid	
STANDARD TIRES					
Tire Capacity (lbs.) each	Tubeless SBR P205/75R15 1453	Tubeless SBR P215/75R15 1583	Tubeless SBR P215/75R15 1583	Tubeless SBR P215/75R15 1583	
Front/ Rear					
Inflation (psi) Max.	35	35	35	35	
Revolutions per mile @ 45 MPH	769	753	753	753	
WHEELS					
Size (in.) Front/Rear	15.0 x 6.0	15.0 x 6.0	15.0 x 6.0	15.0 x 6.0	
Capacity (lbs.) each	1575	1575	1575	1575	
Bolt Holes	5	5	5	5	
Bolt Circle Diameter (in.)	5	5	5	5	
Offset (mm)	13	13	13	13	

¹Based on Curb Weight.

STEERING AND BRAKES

ASTRO PASSENGER VAN

KEY: -- Not Available BW - Blackwall WOL - White Outline Lettered
 AS - All-Season WW - Whitewall
 SBR - Steel-Belted Radial Ply WL - White Lettered

TIRES												
TIRE SIZE	TYPE	RPO	PLY	LOAD RANGE	TIRE CAPACITY (LBS. EA.)	INFLATION (PSI) MAX.	WHEEL SIZE (IN.)	WHEEL CAPACITY (LBS. EA.)	BOLT HOLES	BOLT CIRCLE DIA. (IN.)	OFFSET (MM)	REV. PER MILE @ 45 MPH
P205/75R15	AS/SBR/BW	QCE	--	--	1453	35	15.0 x 6.0	1575	5	5	13	769
P205/75R15	AS/SBR/WL	QCF	--	--	1453	35	15.0 x 6.0	1575	5	5	13	769
P205/75R15	AS/SBR/WW	QCG	--	--	1453	35	15.0 x 6.0	1575	5	5	13	769
P215/75R15	AS/SBR/BW	QCU	--	--	1583	35	15.0 x 6.0	1575	5	5	13	753
P215/75R15	AS/SBR/WW	QCV	--	--	1583	35	15.0 x 6.0	1575	5	5	13	753
P215/75R15	AS/SBR/WL	QCW	--	--	1583	35	15.0 x 6.0	1575	5	5	13	753
P245/60R15 ¹	AS/SBR/WOL	QWT	--	--	1593	35	15.0 x 6.5	1575	5	5	13	784

¹ Requires FE3 Suspension or BYP Sport Package.

OPTIONAL WHEELS						
RPO	DESCRIPTION	WHEEL SIZE (IN.)	CAPACITY	BOLT HOLES	BOLT CIRCLE DIA. (IN.)	OFFSET (MM)
PF3	Wheels - Aluminum (and Special Hub Caps)	15.0 x 6.5	1575	5	5	10
ZJ7	Wheels - Rally (Included w/BYP Sport Pkg., YC6 CL, YC7 LT or FE3 Suspension; Rally Wheels Include Special Hub Caps and Trim Rings)	15.0 x 6.5	1575	5	5	10

MODEL	ASTRO PASSENGER VAN	ASTRO EXTENDED PASSENGER VAN	ASTRO ALL-WHEEL DRIVE PASSENGER VAN	ASTRO ALL-WHEEL DRIVE EXTENDED PASSENGER VAN
MODEL NUMBER	CM10906	CM11006	CL10906	CL11006

STEERING				
Type	Integral Power	Integral Power	Integral Power	Integral Power
Steering Ratio (Variable)	16/13:1	16/13:1	16/13:1	16/13:1
Turning Diameter Curb-to-Curb (ft.)	39.5	39.5	40.5	40.5
Wall-to-Wall (ft.)	40.5	40.5	41.5	41.5



BRAKES				
GVWR (lbs.)	5700	5950	5950	6100
Type	Vacuum Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System	Hydraulic Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System	Hydraulic Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System	Hydraulic Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System
Booster (Diaphragm Diameter) (in.)	7.9 x 7.9 Tandem	Hydra-boost	Hydra-boost	Hydra-boost
Front Rotor Size (Diameter x Thickness) (in.)	11.86 x 1.04	11.57 x 1.25	11.57 x 1.25	11.57 x 1.25
Front Facing Contact Per Axle (sq. in.)	37.9	34.8	34.8	34.8
Rear Drum Size (Diameter x Width) (in.)	9.5 x 2.0	9.5 x 2.0	9.5 x 2.0	9.5 x 2.0
Rear Facing Contact Per Axle (sq. in.)	64.7	64.7	64.7	64.7
Parking Brake Type	Cable to Rear Wheels	Cable to Rear Wheels	Cable to Rear Wheels	Cable to Rear Wheels

ASTRO PASSENGER VAN

MODEL	ASTRO PASSENGER VAN (ALL MODELS)	
MODEL NUMBER	CM10906/CM11006/CL10906/CL11006	
ELECTRICAL		
ENGINE STD	4.3L V6	
STANDARD BATTERY		
Cold Cranking Amps @ 0° F	630	
@ -20° F	470	
Reserve Capacity Min. @ 80° F	115	
STANDARD ALTERNATOR		
Max. Capacity (Amps)	100	
Max Watts @ 12 Volts	1200	
Nominal Amp @ Idle (approx.)	36	
Drive Pulley Ratio	3.2:1	
Model Number	CS130	
OPTIONAL ALTERNATOR¹		
	C69 Front/Rear Air	
Max. Capacity (Amps)	105	
Max Watts @ 12 Volts	1260	
Nominal Amp @ Idle (approx.)	42	
Drive Pulley Ratio	3.2:1	
Model Number	CS130	

¹ NOTE: Alternator is available only as part of Noted RPO.

ALTERNATOR CURVES




COOLING

MODEL	ASTRO PASSENGER VAN (ALL MODELS)	
MODEL NUMBER	CM10906/CM11006/CL10906/CL11006	
STANDARD COOLING SYSTEM		
ENGINE	4.3L	4.3L H.P.
Radiator Thickness (in.)	.93	1.36
System Capacity (gal.)	3.4	3.4
Fan-No. Blades x Dia. x Pitch (in.)	3 x 18 x 2.72	3 x 18 x 2.72
OPTIONAL COOLING SYSTEMS		
OPT. AIR CONDITIONING	V01 ¹	—
Radiator Thickness (in.)	.93	—
System Capacity (gal.)	3.4	—
Fan-No. Blades x Dia. x Pitch (in.)	5 x 19 x 2.64	—
OPT. H.D. RADIATOR AND TRANS. OIL COOLER	C60 ²	C60 ²
Radiator Thickness (in.)	.93	1.36
System Capacity (gal.)	3.4	3.4
Fan-No. Blades x Dia. x Pitch (in.)	5 x 19 x 2.64	5 x 19 x 2.64
OPT. H.D. RADIATOR AND TRANS. OIL COOLER	V02	—
Radiator Thickness (in.)	.93	—
System Capacity (gal.)	3.4	—
Fan-No. Blades x Dia. x Pitch (in.)	5 x 19 x 2.64	—

¹ w/o V02 Cooling, Includes V01 Cooling

² Included w/Z82 Trailering

MODEL		ASTRO PASSENGER VAN	ASTRO EXTENDED PASSENGER VAN	ASTRO ALL-WHEEL DRIVE PASSENGER VAN	ASTRO ALL-WHEEL DRIVE EXTENDED PASSENGER VAN
MODEL NUMBER		CM10906	CM11006	CL10906	CL11006
EXTERIOR DIMENSIONS					
BODY					
Wheelbase (in.)	WB	111.0	111.0	111.0	111.0
Overall Length (in.)	OAL	176.8	186.8	176.8	186.8
Overall Height Nominal (in.)	OAH	76.2	76.2	76.2	76.2
Maximum Width (in.)	OAW	77.5	77.5	77.5	75.5
Bumper To Axle (in.) Front/Rear	BA	30.6/35.2	30.6/45.2	30.6/35.2	30.6/45.2
Ground To Top of Rear Load Floor (in.)	—	24.4	24.6	24.4	24.6
Ground Clearance (in.) Front/Rear	—	7.8/7.3	7.8/7.3	7.6/7.3	7.6/7.3
SIDE LOAD DOOR Opening Height/Width (in.)	—	44.5/34.5	44.5/34.5	44.5/34.5	44.5/34.5
REAR LOAD DOOR Opening Height/Width (in.)	—	44.7/57.0	44.7/57.0	44.7/57.0	44.7/57.0
Step Up Height (in.) Front Door	—	16.3	16.3	16.3	16.3
Side Sliding Door	—	17.4	17.4	17.4	17.4
SIGN PANEL AREA Side Panel/Front Door (in.)	Shaded Area	18 x 80.5/18 x 35	18 x 90.5/18 x 35	18 x 80.5/18 x 35	18 x 90.5/18 x 35
INTERIOR DIMENSIONS					
Head Room (in.) Front/Middle/Rear	HR	39.2/37.9/38.3	39.2/37.9/38.3	39.2/37.9/38.3	39.2/37.9/38.3
Leg Room (in.) Front/Middle/Rear	LR	41.6/36.5/38.5	41.6/36.5/38.5	41.6/36.5/38.5	41.6/36.5/38.5
Shoulder Room (in.) Front/Middle/Rear	SR	64.0/67.8/67.8	64.0/67.8/67.8	64.0/67.8/67.8	64.0/67.8/67.8
Hip Room (in.) Front/Middle/Rear	HP	64.9/50.9/50.9	64.9/50.9/50.9	64.9/50.9/50.9	64.9/50.9/50.9
Load Floor Length (in.) w/Front/Middle/Rear Seats	LFL	88.9/51.4/24.1	98.9/61.4/34.1	88.9/51.4/24.1	98.9/61.4/34.1
Interior Height (in.)	IH	47.5	47.5	47.5	47.5
Interior Width Between Wheelhousings (in.)	IWW	51.6	51.6	51.6	51.6
Cargo Volume (cu. ft.) w/Front/Middle/Rear Seats	CV	151.8/85.8/22.7	170.4/104.4/41.3	151.8/85.8/22.7	170.4/104.4/41.3
FUEL TANK					
Std. Tank Nominal (gal.)		27.0	27.0	27.0	27.0
Location of Tank		Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle
Location of Filler		Left Side	Left Side	Left Side	Left Side



ASTRO PASSENGER VAN

KEY: S - Standard
O - Optional
— Not Available

1. ASTRO PASSENGER VAN (CM10906)
2. ASTRO EXTENDED PASSENGER VAN (CM11006)
3. ASTRO AWD PASSENGER VAN (CL10906)
4. ASTRO AWD EXTENDED PASSENGER VAN (CL11006)

NOTE: Refer to Dealer Order Guide for updated option availability.

				MODELS			
OPTION		CODE	DESCRIPTION	2-WHEEL DRIVE		ALL-WHEEL DRIVE	
			RESTRICTIONS	1	2	3	4
AIR CONDITIONING							
Front		C60	w/o V02 Cooling Incl V01 Cooling				
Front and Rear		C69	Incl w/C69 Front and Rear Air	O	O	O	O
			Incl C60 Front Air, 105 Amp Alternator	O	O	O	O
AXLE, REAR		G80	Locking Differential	O	O	O	O
			N/A with FE3 or BYP Sport Pkg				
BUMPER EQUIPMENT							
		VE5	Front and Rear Chromed w/Rub Strip	O	O	O	O
		VE6	Painted Front and Rear w/Color Keyed End Caps	O	O	O	O
			Incl w/YC6, YC7 or BYP Sport Pkg				
CARRIER LUGGAGE		V54	Black	O	O	O	O
COLD CLIMATE PACKAGE		V10	Incl Engine Block Heater and Coolant Protection	O	O	O	O
CONSOLE, ROOF		DK6		O	O	O	O
			Reqs TR9 Lighting				
CONVENIENCE GROUP		ZQ2	Incl Power Windows and Power Door Locks	O	O	O	O
		ZQ3	Incl Comfortilt Steering and Electronic Speed Control	O	O	O	O
COOLING SYSTEM							
Engine Oil Cooler		KC4	Incl w/Z82 Trailing	O	O	O	O
Radiator		V01	Incl w/C60 or C69 Air	O	O	O	O
H.D. Radiator and Transmission Oil		V02	Incl w/Z82 Trailing	O	O	O	O
			Reqs V01 or V02 Cooling				
			N/A V02 Cooling				
DOOR LOCK SYSTEM, POWER		AU3	Incl w/ZQ2 Conv Pkg	O	O	O	O
DOOR, REAR		E54	Split Panels, includes Rear Window Wiper/Washer	O	O	O	O
			(See Powertrains)				
ENGINES							
4.3-liter EFI V6		LB4		S	S	—	—
4.3-liter CPI V6 H.P.		L35		O	O	S	S
GLASS ARRANGEMENTS		ZW6	Complete Body Incl w/YC7 LT	O	O	O	O
			N/A CM10906 with BYP Sport Pkg				
GLASS TINTING		AJ1	Deep Tinted, Incl w/YC7 LT	O	O	O	O
HEATER		C36	Rear	O	O	O	O
INSTRUMENTATION, ELECTRONIC		U52	Electronic Readout Voltmeter, Temperature, Oil Pressure, Fuel, Speedometer, Tachometer	O	O	O	O
LIGHTING, AUXILIARY		TR9	Incl w/YC6 or YC7, Incl Front and Rear Dome and Reading Lamps, Courtesy Light Switches on all Doors, Front/Rear Stepwell Lights and Glove Box Light.	O	O	O	O
LUXURY PACKAGE (CL)		YC6	(See Trim Level Section)	O	O	O	O
LUXURY TOURING PACKAGE (LT)		YC7	(See Trim Level Section)	O	O	O	O
MIRRORS							
Exterior, Below-Eye-Line Type		D44	Black L.H. 5.0" x 8.5" R.H. 5 1/4" x 9"	O	O	O	O
Exterior, Electric Remote		D48	L.H. 5.0" x 8.5" R.H. 5 1/4" x 9"	O	O	O	O
PAINT, EXTERIOR			(See Color and Trim)				
Solid		ZY1	Solid	S	S	S	S
Custom Two-Tone		ZY2	Incl Body Side Molding Reqs VE5/VE6 Bumper	O	O	O	O
Special Two-Tone		ZY3	w/YC7 LT Incl Body Side Molding	O	O	O	O
Deluxe Two-Tone		ZY4	Incl Body Side Molding and Body Striping Reqs VE5 Bumper w/o YC6	O	O	O	O
RADIO EQUIPMENT							
Electronically-Tuned AM/FM Stereo Radio w/Seek-Scan and Digital Clock		UM7	14 Presets, Digital Display, two 6" ERS Front Speakers, two 6" ERS Rear Speakers, two 4" Rear Speakers, 33 Watts Total Power Output.	O	O	O	O
Electronically-Tuned AM/FM Stereo Radio w/Seek-Scan, Stereo Cassette Tape and Digital Clock		UM6	14 Presets, Digital Display, two 6" ERS Front Speakers, two 6" ERS Rear Speakers, 33 Watts Total Power Output.	O	O	O	O
Electronically-Tuned AM Stereo/FM Stereo Radio w/Seek-Scan, Stereo Cassette Tape with Search and Repeat, Graphic Equalizer and Digital Clock		UX1	14 Presets, Digital Display, two 6" ERS Front Speakers, two 6" ERS Rear Speakers, two 4" Rear Speakers, 33 Watts Total Power Output	O	O	O	O
Electronically Tuned AM/FM Stereo Radio w/Seek-Scan, Compact Disc Player & Clock		U1C		O	O	O	O
Radio Delete		UL5		O	O	O	O

OPTIONS

KEY: S - Standard
O - Optional
— Not Available

1. ASTRO PASSENGER VAN (CM10906)
2. ASTRO EXTENDED PASSENGER VAN (CM11006)
3. ASTRO AWD PASSENGER VAN (CL10906)
4. ASTRO AWD EXTENDED PASSENGER VAN (CL11006)

NOTE: Refer to Dealer Order Guide for updated option availability.

				MODELS			
				2-WHEEL DRIVE		ALL-WHEEL DRIVE	
OPTION	CODE	DESCRIPTION	RESTRICTIONS	1	2	3	4
SEATING ARRANGEMENTS							
5 Person Seating	ZP5	2 Front High Back Buckets and Standard removable 3-Passenger Bench		S	S	S	S
7 Person Seating	ZP7	4 High Back Bucket Seats and a removable 3-Passenger Bench; Incls A78 Seat Back Recliner		O	O	O	O
8 Person Seating	ZP8	2 High Back Bucket Seats and Two removable 3-Passenger Bench Seats; YC7 LT Adds Reclining Seat Backs and Split Bench Seats		O	O	O	O
SEAT BACK RECLINER AND DUAL ARMRESTS	A78	Incl w/ZP7 Seating; or YC7 LT	Reqs Custom Trim	O	O	O	O
SEAT, 6-WAY POWER, DRIVER	AC3		Reqs A78 Seat Back Recliner, ZP7 or YC7 LT	O	O	O	O
SPORT PACKAGE	BYP	Incls Air Dam w/Fog Lamps, FE3 Sport Suspension, Color Keyed Front & Rear Bumpers and a Wide Black Body Side Molding w/Red Insert and Grille w/Red Striping	Incls ZW6 glass with CM11006. N/A YC7 LT; N/A ZW6 Glass with CM10906. Reqs ZY1 or ZY2 paint	O	O	—	—
STOWAGE COMPARTMENT	BA8	Drawer-type, non-locking type beneath front passenger seat		O	O	O	O
SUSPENSION, SPORT	FE3	Incls ZJ7 Wheels, QWT P245/60R15 White Outlined Lettered Tires, Rear Stabilizer & Front & Rear Gas Shocks Incl w/BYP Sport Pkg		O	O	—	—
TIRE EQUIPMENT							
P205/75R15	QCE	(See Wheels and Tires for Details)	N/A FE3 Susp or BYP Sport Package	S	—	—	—
P205/75R15	QCF		N/A FE3 Susp or BYP Sport Package	O	—	—	—
P205/75R15	QCG		N/A FE3 Susp or BYP Sport Package	O	—	O	—
P215/75R15	QCU		N/A FE3 Susp or BYP Sport Package	—	S	S	S
P215/75R15	QCV		N/A FE3 Susp or BYP Sport Package	—	O	O	O
P215/75R15	QCW		N/A FE3 Susp or BYP Sport Package	—	O	O	O
P245/60R15	QWT		Reqs FE3 Susp or BYP Sport Package	O	O	—	—
TRAILERING SPECIAL EQUIPMENT							
Heavy-Duty	Z82	Incls Trailering Hitch and Wiring Harness; Incls V02 and KC4 Engine Oil Cooler and Heavy-Duty Flasher	CM10906 or CM11006 w/ LB4 Eng reqs 3.42 or 3.73 Rear Axle; CL10906 or CL11006 reqs 3.73 Rear Axle	O	O	O	O
Light-Duty	Z72	Incls Trailer Hitch and Wiring Harness	Reqs V01 or V02 Cooling	O	O	O	O
TRANSMISSIONS							
4-Speed Automatic w/Overdrive	MX0	(See Powertrains)		S	S	S	S
WHEELS							
Aluminum	PF3	On YC7 LT Color-Keyed		O	O	O	O
Rally	ZJ7	Incl w/BYP Sports Pkg, YC6, YC7 or FE3. Incls Special Hub Caps and Trim Rings		O	O	O	O


ASTRO PASSENGER VAN

SOLID COLORS

(ZY1)

WITHOUT LUXURY TOURING PACKAGE

Solid paint (ZY1) is standard on all models. All painted areas of the body and front end sheet metal, including the bumpers, are the same color. Below are the interior trim color and exterior paint combinations recommended by Chevrolet, however any available interior trim color may be ordered. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.



KEY: — Not Available ● Recommended Blank—Available WHEEL COLOR LEGEND: S - Silver, B - Beige, W - White.

EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS				WHEEL COLORS	
COLOR 1	COLOR 2		Blue	Garnet	Beige	Gray	Aluminum	Rally
10 Ivory White	10	—	●	●	●	●	W	S
15 Sterling Silver Met.	15	—	●	●		●	S	S
16 Fieldstone Gray Met.	16	—		●		●	S	S
27 Smoke Blue Met.	27	—	●			●	S	S
30 Catalina Blue Met.	30	—	●			●	S	S
34 Light Teal Met.	34	—				●	S	S
41 Onyx Black	41	—	●	●	●	●	S	S
57 Sand Beige Met.	57	—		●	●		B	B
75 Deep Red Met.	75	—		●	●		S	S
76 Burnt Red Met.	76	—		●	●	●	S	S

WITH LUXURY TOURING PACKAGE (YC7) ONLY

(Includes Decal Striping)

Below are the interior trim color and exterior paint combinations recommended by Chevrolet. They are the only available interior and exterior combinations allowed. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.


KEY: — Not Available ● Recommended WHEEL COLOR LEGEND: S - Silver, B - Beige

EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS		WHEEL COLORS	
COLOR 1	COLOR 2		Beige	Gray	Aluminum	Rally
36 Teal Blue Met.	36	Teal	—	●	S	S
76 Burnt Red Met.	76	Silver	—	●	S	S
76 Burnt Red Met.	76	Beige	●	—	B	B
97 Slate Met.	97	Silver	—	●	S	S

CUSTOM TWO-TONE

(ZY2) (Includes Body Side Molding)

Custom two-tone paint (ZY2) is available on all models (except on Astro LT). Color code 1 is applied to the area above the bodyside molding, and Color code 2 is applied to the areas below the bodyside molding. Below are the interior trim color and exterior paint combinations recommended by Chevrolet. The only available Color code 1/Color code 2 exterior color combinations are those shown in the chart below, however any available interior trim color may be ordered. For further information, refer to Seats and Interior Trim as well as the Order Guide.



KEY: ●—Recommended Blank—Available WHEEL COLOR LEGEND: S - Silver, W-White, B - Beige


EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS				WHEEL COLORS	
COLOR 1	COLOR 2		Blue	Garnet	Beige	Gray	Aluminum	Rally
10 Ivory White	27 Smoke Blue Met.	Vermillion/Silver/Vermillion	●			●	S	S
	30 Catalina Blue Met.	Vermillion/Silver/Vermillion	●			●	S	S
	34 Light Teal Met.	Vermillion/Silver/Vermillion				●	S	S
	41 Onyx Black	Vermillion/Silver/Vermillion		●		●	W	S
	75 Deep Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
	76 Burnt Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
15 Sterling Silver Met.	30 Catalina Blue Met.	Blue/Silver/Blue	●				S	S
	34 Light Teal Met.	Vermillion/Silver/Vermillion				●	S	S
	75 Deep Red Met.	Black/Red/Black		●		●	S	S
	76 Burnt Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
16 Fieldstone Gray Met.	41 Onyx Black	Silver/Red/Silver		●		●	S	S
	75 Deep Red Met.	Silver/Red/Silver		●		●	S	S
	76 Burnt Red Met.	Silver/Red/Silver		●		●	S	S
27 Smoke Blue Met.	10 Ivory White	Vermillion/Silver/Vermillion	●			●	W	S
	30 Catalina Blue Met.	Blue/Silver/Blue	●			●	S	S
30 Catalina Blue Met.	10 Ivory White	Vermillion/Silver/Vermillion	●				W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion	●			●	S	S
	27 Smoke Blue Met.	Blue/Silver/Blue	●			●	S	S
	57 Sand Beige Met.	Black/Beige/Black	●				B	B
34 Light Teal Met.	10 Ivory White	Vermillion/Silver/Vermillion				●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion				●	S	S
41 Onyx Black	10 Ivory White	Vermillion/Silver/Vermillion		●		●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	27 Smoke Blue Met.	Blue/Silver/Blue	●				S	S
	57 Sand Beige Met.	Black/Beige/Black			●		B	B
57 Sand Beige Met.	41 Onyx Black	Vermillion/Silver/Vermillion			●		B	B
	75 Deep Red Met.	Black/Red/Black		●	●		B	B
	76 Burnt Red Met.	Black/Red/Black		●	●		B	B
75 Deep Red Met.	10 Ivory White	Black/Red/Black				●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	57 Sand Beige Met.	Black/Beige/Black		●		●	B	B
	76 Burnt Red Met.	Silver/Red/Silver		●		●	S	S
76 Burnt Red Met.	10 Ivory White	Vermillion/Silver/Vermillion		●		●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	57 Sand Beige Met.	Black/Beige/Black		●	●		B	B
	75 Deep Red Met.	Silver/Red/Silver		●		●	S	S

SPECIAL TWO-TONE

(ZY3) (Includes Decal Striping and Body Side Molding)

Special two-tone paint (ZY3) is available with the Luxury Touring Package (YC7) only. It includes a dual color decal stripe and black body side molding. Color code 1 is applied to the areas above the belt styling crease line. Color code 2 is applied to the areas below the belt styling crease line. Below are the interior trim color and exterior paint combinations recommended by Chevrolet. They are the only available interior and exterior combinations allowed. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.

WITH LUXURY TOURING PACKAGE (YC7) ONLY




KEY: — Not Available ● Recommended WHEEL COLOR LEGEND: S - Silver, B - Beige

EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS		WHEEL COLORS	
COLOR 1	COLOR 2		Beige	Gray	Aluminum	Rally
16 Fieldstone Gray Met.	97 Slate Met.	Silver	—	●	S	S
34 Light Teal Met.	36 Teal Blue Met.	Teal	—	●	S	S
57 Sand Beige Met.	76 Burnt Red Met.	Beige	●	—	B	B
76 Burnt Red Met.	57 Sand Beige Met.	Beige	●	—	B	B

DELUXE TWO-TONE

(ZY4) (Includes Body Side Molding)

Deluxe two-tone paint (ZY4) is available on all models (except Astro LT). Color code 1 is applied to the areas above the decal striping and below the bodyside molding. Color code 2 is applied to the area in between bodyside molding and decal. Below are the interior trim color and exterior paint combinations recommended by Chevrolet. The only available color code 1/color code 2 exterior color combinations are those shown in the chart below, however, any available interior trim color may be ordered. For further information refer to Seats and Interior Trim pages as well as the Ordering Guide.



KEY: ●—Recommended Blank—Available WHEEL COLOR LEGEND: S - Silver, W-White, B - Beige


EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS				WHEEL COLORS	
COLOR 1	COLOR 2		Blue	Garnet	Beige	Gray	Aluminum	Rally
10 Ivory White	27 Smoke Blue Met.	Vermillion/Silver/Vermillion	●			●	S	S
	30 Catalina Blue Met.	Vermillion/Silver/Vermillion	●			●	S	S
	34 Light Teal Met.	Vermillion/Silver/Vermillion				●	S	S
	41 Onyx Black	Vermillion/Silver/Vermillion		●		●	W	S
	75 Deep Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
	76 Burnt Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
15 Sterling Silver Met.	30 Catalina Blue Met.	Blue/Silver/Blue	●				S	S
	34 Light Teal Met.	Vermillion/Silver/Vermillion				●	S	S
	75 Deep Red Met.	Black/Red/Black		●		●	S	S
	76 Burnt Red Met.	Vermillion/Silver/Vermillion		●		●	S	S
16 Fieldstone Gray Met.	41 Onyx Black	Silver/Red/Silver		●		●	S	S
	75 Deep Red Met.	Silver/Red/Silver		●		●	S	S
	76 Burnt Red Met.	Silver/Red/Silver		●		●	S	S
27 Smoke Blue Met.	10 Ivory White	Vermillion/Silver/Vermillion	●			●	W	S
	30 Catalina Blue Met.	Blue/Silver/Blue	●			●	S	S
30 Catalina Blue Met.	10 Ivory White	Vermillion/Silver/Vermillion	●				W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion	●			●	S	S
	27 Smoke Blue Met.	Blue/Silver/Blue	●			●	S	S
	57 Sand Beige Met.	Black/Beige/Black	●				B	B
34 Light Teal Met.	10 Ivory White	Vermillion/Silver/Vermillion				●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion				●	S	S
41 Onyx Black	10 Ivory White	Vermillion/Silver/Vermillion		●		●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	27 Smoke Blue Met.	Blue/Silver/Blue	●				S	S
	57 Sand Beige Met.	Black/Beige/Black			●		B	B
57 Sand Beige Met.	41 Onyx Black	Vermillion/Silver/Vermillion			●		B	B
	75 Deep Red Met.	Black/Red/Black		●	●		B	B
	76 Burnt Red Met.	Black/Red/Black		●	●		B	B
75 Deep Red Met.	10 Ivory White	Black/Red/Black				●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	57 Sand Beige Met.	Black/Beige/Black		●		●	B	B
	76 Burnt Red Met.	Silver/Red/Silver		●		●	S	S
76 Burnt Red Met.	10 Ivory White	Vermillion/Silver/Vermillion		●		●	W	S
	15 Sterling Silver Met.	Vermillion/Silver/Vermillion		●		●	S	S
	57 Sand Beige Met.	Black/Beige/Black		●	●		B	B
	75 Deep Red Met.	Silver/Red/Silver		●		●	S	S

ASTRO PASSENGER VAN

SPORT COLORS

(ZY1)

Solid paint (ZY1) is available on the Astro Sport. All painted areas of the body and front end sheet metal, including the bumpers, are the same color. Below are the interior trim color and exterior paint combinations recommended by Chevrolet, however any available interior trim color may be ordered. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.




KEY: — Not Available ● Recommended Blank—Available WHEEL COLOR LEGEND: S - Silver, B - Beige, W - White

EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS				WHEEL COLORS	
COLOR 1	COLOR 2		Blue	Garnet	Beige	Gray	Aluminum	Rally
10 Ivory White	10	—				●	W	S
15 Sterling Silver Met.	15	—				●	S	S
27 Smoke Blue Met.	27	—	●				S	S
41 Black Onyx	41	—		●		●	S	S
57 Sand Beige Met.	57	—			●		B	B
75 Deep Red Met.	75	—		●			S	S

(ZY2)

Custom two-tone paint (ZY2) is available on the Astro Sport. Below are the interior trim color and exterior paint combinations recommended by Chevrolet, however any available interior trim color may be ordered. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.




KEY: — Not Available Blank—Available ● Recommended WHEEL COLOR LEGEND: S - Silver, B - Beige, W - White

EXTERIOR COLORS		STRIPE COLORS	INTERIOR COLORS				WHEEL COLORS	
COLOR 1	COLOR 2		Blue	Garnet	Beige	Gray	Aluminum	Rally
10 Ivory White	41 Onyx Black	—				●	W	S
15 Sterling Silver Met.	41 Onyx Black	—				●	S	S
27 Smoke Blue Met.	41 Onyx Black	—	●				S	S
57 Sand Beige Met.	41 Onyx Black	—			●		B	B
75 Deep Red Met.	41 Onyx Black	—		●			S	S

SPECIAL TRAILERING PACKAGES

If you tow a light trailer (up to 2000 lbs. gross weight) with your new Astro Passenger Van, Special Trailing Package (RPO Z72) is recommended. RPO Z72 includes a dead-weight hitch which is bolted to the rear bumper and includes a 1 7/8"-diameter hitch ball. This package also includes a 5-wire wiring harness that requires a connector. This allows the electrical system to activate trailer lights and other electrical systems.

If you intend to tow a medium trailer (2000 to 4000 lbs. gross weight) or a heavy trailer (4000 to 6000 lbs. gross weight), the heavy-duty Special Trailing Package RPO Z82 is a required option. (This Z82 option is also required, regardless of gross trailer weight, if your trailer tongue weight exceeds 200 lbs.) RPO Z82 includes a weight-distributing hitch platform which is bolted to the undercarriage. RPO Z82 includes a 7-wire wiring harness that requires a connector. With either trailing package, the wiring harness comes coiled and tied, with connecting end stored on the floor in the right-hand rear corner compartment.



See the chart below — Required/Recommended Trailing Equipment — for trailing options in addition to Trailing Special Packages.

The chart below indicates the trailing equipment required for light, medium and heavy trailer towing. Additional recommended options are also indicated. To help

you in ordering, each column lists Regular Production Option (RPO) numbers.

NOTE: Other important trailing information is available in the Owner's Manual of every 1992 Astro Passenger Van.

(R) --- Required

REQUIRED/RECOMMENDED TRAILERING EQUIPMENT

Hitch Type	Ball					
	Light		Medium		Heavy	
Trailer Classification	2000		4000		6000	
Maximum Trailer Weight (lbs.)	200		500		750	
Maximum Tongue Load (lbs.)	200		500		750	
Vehicle Series	2WD	AWD	2WD	AWD	2WD	AWD
Engine and Axle Ratio with (Maximum Trailer Weight)	4.3L		3.23		3.42	
	3.23	3.42	3.23	3.42	3.42 (5500) 3.73 (6000)	3.42 (5500) 3.73 (6000)
Special Trailing Package	Z72	Z72	Z82(R)	Z82(R)	Z82(R)	Z82(R)
Trailer Hitch	Deadweight		Z72		Z72	
	(Weight Distributing) Platform		Z82(R)		Z82(R)	
Wiring Harness	5 wire		Z72		Z72	
	7 wire		Z82(R)		Z82(R)	
Cooling	H.D. Radiator		VO1(R)		VO1(R)	
	Transmission Oil		Z82(R)		Z82(R)	
	Engine Oil		Z82(R)		Z82(R)	
Locking Rear Axle	G80		G80		G80	
Cruise Control & Tilt Wheel	ZQ3		ZQ3		ZQ3	

Trailing Related Standard Equipment:
Power Steering, Power Brakes, 27 Gallon Fuel Tank, 100 Amp Alternator, Heavy Duty Shocks, Front Stabilizer Bar, 4-Speed Automatic Transmission.

HOW TO USE GCWRs TO DETERMINE POWERTRAIN AND REAR AXLE RATIO FOR TRAILERING

Use Gross Combination Weight Ratings (GCWRs) to determine the engine, transmission and rear axle ratio you will require to tow a trailer with your truck. The chart below shows you the maximum allowable GCWR based on all the available truck engines and rear axle ratios with automatic or manual transmissions.

The GCWR includes the total loaded weight of both the truck and trailer. Any available engine may be used for trailering if the GCWR shown is not exceeded. The trailer weight can be increased by 25% if the vehicle speed will not exceed 25 mph.

GROSS COMBINATION WEIGHT RATING (GCWR)																				
GCWR (lb.)	6000	6500	7000	7500	8000	8500	9000	9500	10,000	10,500	11,000	11,500	12,000	12,500	13,500	14,000	14,500	15,000	16,000	19,000
Engines	Rear Axle Ratios																			
4.3L (262) V6 Gas							3.23	3.42	3.73											
H.P. 4.3L (262) V6 Gas								3.42	3.73											

When towing a trailer in excess of 4000 lbs. with a truck equipped with a 4-speed automatic transmission, it is recommended to shift to third gear range ("D") instead of overdrive ("O") for normal towing, and to manually downshift as required on uphill and downhill grades.

NOTE: Model and driveline combinations must be verified by your local dealer for correct emissions equipment.

GENERAL TRAILERING INFORMATION

Chevrolet Trucks offer a wide selection of available options for trailering and a few of them are illustrated and described here.

WIRING HARNESES

5-wire used with trailers up to 2000 lbs. gross weight and 7-wire for larger trailers. Harnesses tie into vehicle's electrical system to give your trailer lights, plus electric brakes or battery charging.

HITCH BALLS

1 $\frac{7}{8}$ "-diameter ball is standard with light-duty hitches.

TRUCK WIRING CODE

The following color code for trucks should be used when installing trailer wiring harnesses.

- **Blue.** Used for electric trailer brakes or auxiliary wiring.
- **Red.** Used for battery charging. Connects to starter solenoid. (7-wire harness only).
- **Light Green.** Backup lights (7-wire harness only).
- **Brown.** Taillight and running lights.
- **Yellow.** Left stop and turn signal.
- **Dark Green.** Right stop and turn signal.
- **White.** Ground.



COOLERS AND COOLING

To maintain normal temperatures in coolant, engine and transmission oil, order the following separate options.

RPO V02. This is an extra-capacity heavy-duty automatic transmission oil cooler option. (Included in RPO Z82 Special Trailering Package.)

RPO KC4. This optional engine oil cooler circulates oil through a separate cooler mounted on the LH side of the radiator. (Included in RPO Z82 Trailering Package.)

ASTRO CARGO VAN




CONTENTS


	Page
MODELS	2
SEATING AND WINDOW ARRANGEMENTS	3
STANDARD TRIM	4
POWERTRAINS	5
STANDARD SUSPENSION	6
OPTIONAL SUSPENSION	7
WHEELS AND TIRES	8
STEERING/BRAKES	8
ELECTRICAL	9
COOLING	10
DIMENSIONS	11
OPTIONS	12
COLOR COMBINATIONS	14
EXTERIOR COLORS	B
INTERIOR TRIM	C
SEATS	D
TRAILERING	E

ASTRO CARGO VAN

TWO-WHEEL DRIVE MODELS


ASTRO CARGO VAN 	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX' PAYLOAD (LBS.)	PASS. CAP. (STD/OPT)	STD ENGINE/ TRANS	OPT ENGINE/ TRANS
	CM10905/ZW9	111	5000	1446	1/2	4.3L V6/A4	4.3L H.P. V6/A4
	CM10905/ZW9/G50	111	5400	1841	1/2	4.3L V6/A4	4.3L H.P. V6/A4

ASTRO CARGO VAN
The Astro Cargo Van is offered in one wheelbase with a selection of GVWRs.


ASTRO EXTENDED CARGO VAN 	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX' PAYLOAD (LBS.)	PASS. CAP. (STD/OPT)	STD ENGINE/ TRANS	OPT ENGINE/ TRANS
	CM11005/ZW9	111	5600	1982	1/2	4.3L V6/A4	4.3L H.P. V6/A4

ASTRO EXTENDED CARGO VAN
The Astro Extended Cargo Van retains the same 111-in. wheelbase as the regular length model, while adding 10-inches to the rear frame and sheet metal for increased cargo capacity.

ALL-WHEEL DRIVE MODELS

ASTRO ALL-WHEEL DRIVE CARGO VAN 	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX' PAYLOAD (LBS.)	PASS. CAP. (STD/OPT)	STD ENGINE/ TRANS	OPT ENGINE/ TRANS
	CL10905/ZW9 ²	111	5800	1944	1/2	4.3L H.P. V6/A4	—

ASTRO ALL-WHEEL DRIVE CARGO VAN
The Astro All-Wheel Drive Cargo Van offers one GVWR with full-time all-wheel drive.


ASTRO ALL-WHEEL DRIVE EXTENDED CARGO VAN 	MODEL NUMBER	WB (IN.)	GVWR (LBS.)	MAX' PAYLOAD (LBS.)	PASS. CAP. (STD/OPT)	STD ENGINE/ TRANS	OPT ENGINE/ TRANS
	CL11005/ZW9	111	5850	1933	1/2	4.3L H.P. V6/A4	—

ASTRO ALL-WHEEL DRIVE EXTENDED CARGO VAN
The Astro All-Wheel Drive Extended Cargo Van retains the same 111-inch wheelbase as the regular length model, while adding 10-inches to the rear frame and sheet metal for increased cargo capacity.

¹Based on Curb Weight. ² Reqs. QCU/QCV/QCW Tires


SEATING ARRANGEMENTS

STANDARD: 1-PASSENGER SEATING (ZX1)



A driver's high-back bucket seat is standard. It is available in custom Vinyl trim only.


OPTIONAL: 2-PASSENGER SEATING (ZX2)




This option consists of both a driver's and a passenger's high-back bucket seat. It is available in Custom Vinyl or Custom Cloth trim.

WINDOW ARRANGEMENTS


STANDARD



OPTIONAL: w/ZW2
Includes rear door windows



OPTIONAL: w/ZW3
Includes rear door windows, and side cargo door window



OPTIONAL: w/ZW6
Includes rear door windows, side cargo door window, RH rear quarter window and LH front and rear quarter windows



STANDARD

The Astro Cargo Van is designed to offer buyers a high level of standard comfort and several convenience features when purchasing a standard-level cargo van.

The following features are standard.

POWERTRAIN/CHASSIS

- **ALL-WHEEL DRIVE:** CL10905 and CL11005 models only. This system distributes the power delivered to wheels in ratio of 35% to the front wheels and 65% to the rear wheels. On low-traction surfaces a viscous coupling automatically varies this front-to-rear torque ratio to correct traction loss.
- **ALTERNATOR:** 100 Amp Delcotron.
- **BATTERY:** 12 volt, negative ground; 630 Cold Cranking Amps @ 0 degrees F.
- **BRAKES:** Power; vacuum (CM10905 and CM11005). Front—disc. Rear—drum. Includes rear-wheel anti-lock brake system. Power; hydraulic (CL10905 and CL11005). Front—disc. Rear—drum. Includes four-wheel anti-lock braking system.
- **ENGINE:** 4.3-liter Vortec V6 engine with Electronic Fuel Injection (EFI) on 2-wheel drive. It produces 150 net horsepower @ 4000 rpm and 230 lb. ft. of net torque @ 2400 rpm. 4.3-liter Vortec High Performance V6 engine with Central Port Injection on All-Wheel Drive. It produces 200 net horsepower @ 4400 rpm and 260 lb-ft of net torque @ 3600 rpm.
- **EXHAUST:** Single.
- **FRAME:** Integral body frame design with boxed section front stub frame.
- **FUEL TANK:** 27.0-gallon (approx.).
- **REAR AXLE:** Hypoid, Semi-Floating type. Std. ratio: 3.23 on CM10905 and CM11005. 3.42 on CL10905 and CL11005.
- **SHOCK ABSORBERS:** Front and Rear —32 mm piston diameter.
- **STABILIZER BAR:** Front —1.10 inch diameter on CM10905 and CM11005. —1.18 inch diameter on CL10905 and CL11005.
- **STEERING:** Integral Power. Variable Ratio—On Center/At Lock—16/13:1.
- **SUSPENSION:** Front—Independent type with computer selected springs. Rear wheel-drive models incorporate coil springs and all-wheel drive models incorporate torsion bars. Rear—Composite leaf springs.
- **TRANSMISSION:** 4-speed automatic with overdrive.
- **TRANSFER CASE:** CL10905 and CL11005 models.

EXTERIOR

- **AIR DAM:** Black.
- **BUMPER:** Front and rear bumpers painted lower body color, with front bumper guards.
- **COLORS:** Choice of ten exterior colors in a solid paint scheme. See Color and Trim specifications for details.
- **CORROSION PROTECTION:** Underbody.
- **DOORS:** Driver and passenger front side doors, sliding RH side cargo door, and RH and LH rear load doors.
- **GRILLE:** Molded plastic grille painted black.
- **HEADLAMPS:** Single halogen headlamps.
- **HORN:** Dual high-note and low-note electric horn.
- **LICENSE PLATE BRACKET:** Front and rear
- **MIRRORS:** RH and LH exterior rear view mirrors with pivoting arm, adjustable heads and black finish. Mirror head size is 4 3/4" x 7".
- **SPARE TIRE/WHEEL:** Compact spare tire and wheel mounted under floor.
- **TIRES:** Four all-season steel belted radial tires. P205/75R15 on CM10905; P215/75R15 on CL10905, CM11005 and CL11005 models.
- **WHEELS:** Four 15.0" x 6.0" steel wheels painted argent. Includes bright metal hub caps with black trim.

INTERIOR



- **ARMREST:** LH front door.
- **ASSIST HANDLE:** Right hand passenger door pillar
- **BEVERAGE HOLDERS:** Two located on top of engine cover panel
- **CHIMES:** Headlamp warning chime.
- **CIGARETTE LIGHTER:** Includes ashtray lamp located in engine cover panel.
- **COAT HOOKS:** LH coat hook.
- **COLORS:** Choice of Blue or Beige. (Choice of Blue, Beige, Garnet, or Gray when optional front seat is ordered.)
- **DOME LAMP:** Two dome lamps with front door actuated switches.
- **DOOR SILL PLATE:** Black plastic.
- **FLOOR COVERING:** Embossed black rubber front mat (driver side only).
- **FUEL FILLER DOOR:** Remote release, front upper corner driver side stepwell.
- **GAUGES:** Include speedometer, odometer, fuel level, voltmeter, oil pressure, coolant temperature and trip odometer and additional telltale lights.
- **HEADLINER:** Front compartment color-keyed, foam backed cloth.
- **HEATER:** Deluxe heater and windshield defogger with side window defoggers.
- **MIRRORS:** 10-inch rearview mirror. (Requires Glass Package.)
- **RADIO:** Electronically-tuned AM radio with two 6" diameter front dash speakers, and fixed mast antenna. (Please refer to the Delco Electronics brochure in RPO
- Detail for further information.)
- **SEATS:** Driver's high-back bucket seat with custom vinyl trim.
- **STEERING WHEEL:** Black vinyl 4-spoke steering wheel.
- **STOWAGE BOX:** Located in front of engine cover panel
- **SUNSHADES:** RH and LH color-keyed sunshades.
- **TOOLS:** Screw-operated scissor-type jack with ratchet handle and extension and two wheel blocks. Located at right rear of vehicle.
- **WINDOWS:** Tinted.
- **WINDSHIELD WIPERS:** Intermittent.

MODEL	ENGINE	TRANSMISSION	AXLES			GVWR
			ECONOMY		POWER	
			3.23	3.42	3.73	
ASTRO CARGO VAN CM10905/ZW9	4.3L V6 (LB4)	S	S	O	O ¹	5000/5400
ASTRO EXT. CARGO VAN CM11005/ZW9	4.3L V6 (LB4)	S	S	O	O ¹	5600
ASTRO CARGO VAN ALL-WHEEL DRIVE CL10905/ZW9	4.3L V6 H.P. (L35)	S	—	S	O ²	5800
ASTRO EXT. CARGO VAN ALL-WHEEL DRIVE CL11005/ZW9	4.3L V6 H.P. (L35)	S	—	S	O ²	5850

¹Requires Z82 Trailering. ²Requires V02 Cooling and KC4 Engine Oil Cooler.

HORSEPOWER AND TORQUE RATINGS

ENGINE	4.3L V6	4.3L V6 H.P.
RPO CODE	LB4	L35
SAE NET HORSEPOWER Horsepower @ RPM	150 @ 4000	200 @ 4400
SAE NET TORQUE Lb. Ft. @ RPM	230 @ 2400	260 @ 3600
FUEL SYSTEM	EFI	CPI
STD. BATTERY Cold Cranking Amps @ 0° F	630	630



AUTOMATIC TRANSMISSION	
MODEL	AUTOMATIC 4-SPEED w/OVERDRIVE 4L60
RPO CODE	MX0
GEAR RATIOS	
First	3.06
Second	1.63
Third	1.00
Fourth	0.70
Reverse	2.29
GEAR TYPE	Planetary
TORQUE CONVERTER Element Types Lock-up Clutch	Pump/Stator/Turbine Automatic
LUBRICANT CAPACITY (pints) Dry Fill Refill	19 10

AXLES	REAR	FRONT—ALL-WHEEL DRIVE
MAKE AND CAPACITY (lbs.)	GM 3150	GM 3050
PINION & RING GEAR Type	Hypoid	
Ratio	3.23	3.42
Pinion Teeth	13	11
Ring Gear Teeth	42	41
Ring Gear Dia. (in.)	7.5	7.5
DIFFERENTIAL Type	2-Pinion Tapered Roller	
Bearings, Type	Tapered Roller	
AXLE SHAFTS Type	Semi-Floating Integral Shaft and Drive Flange	
Minimum Diameter (in.)	—	
HOUSING @ SPRING SEAT Section Diameter and Thickness (in.)	2.69 x .116-.175	

MODEL	ASTRO CARGO VAN	ASTRO EXTENDED CARGO VAN	ASTRO ALL-WHEEL DRIVE CARGO VAN	ASTRO ALL-WHEEL DRIVE EXT. CARGO VAN
MODEL NUMBER	CM10905/ZW9	CM11005/ZW9	CL10905/ZW9	CL11005/ZW9
STANDARD SUSPENSION				
PAYLOAD (Maximum lbs.) ¹	1446	1982	1944	1933
GVWR (lbs.)	5000	5600	5800	5850
GAWR (lbs.) Front	2800	2800	3050	3050
Rear	2492	3150	2900	3150
FRONT SUSPENSION				
Type	Ind. Coil Spring	Ind. Coil Spring	Torsion Bar	Torsion Bar
Standard Spring Capacity (Total lbs.)	2800	2800	3050	3050
Front Shock Absorbers Piston Diameter (mm)	32	32	32	32
Front Stabilizer Bar Diameter (in.)	1.10	1.10	1.18	1.18
REAR SUSPENSION				
Type	Composite Leaf Spring	Composite Leaf Spring	Composite Leaf Spring	Composite Leaf Spring
Standard Spring Capacity (Total lbs.)	2492	3150	2900	3150
Leaves Per Spring	1	1	1	1
Leaf Total Thickness (in.)	.813	.813	.813	.813
Rear Shock Absorbers Piston Diameter (mm)	32	32	32	32
FRONT AXLE				
Type	—	—	Independent	Independent
Make	—	—	GM	GM
Maximum Capacity (lbs.)	2800	2800	3050	3050
Standard Hub Locks	—	—	Insta-Trac	Insta-Trac
Pinion/Ring Gear Type	—	—	Hypoid	Hypoid
REAR AXLE				
Type	Semi-Floating	Semi-Floating	Semi-Floating	Semi-Floating
Make	GM	GM	GM	GM
Maximum Capacity (lbs.)	3150	3150	3150	3150
Pinion/Ring Gear Type	Hypoid	Hypoid	Hypoid	Hypoid
STANDARD TIRES				
Type	Tubeless AS/SBR P205/75R15	Tubeless AS/SBR P215/75R15	Tubeless AS/SBR P215/75R15	Tubeless AS/SBR P215/75R15
Capacity (lbs.) each	1453	1583	1583	1583
Inflation (psi) max.	35	35	35	35
Revolutions per mile @ 45 mph	769	753	753	753
WHEELS				
Size (in.) Front/Rear	15.0 x 6.0	15.0 x 6.0	15.0 x 6.0	15.0 x 6.0
Capacity (lbs.) each	1575	1575	1575	1575
Bolt Holes	5	5	5	5
Bolt Circle Dia. (in.)	5	5	5	5
Offset (mm)	13	13	13	13

¹Based on Curb Weight.

MODEL	ASTRO CARGO VAN	ASTRO EXTENDED CARGO VAN	ASTRO ALL-WHEEL DRIVE CARGO VAN	ASTRO ALL-WHEEL DRIVE EXT. CARGO VAN
MODEL NUMBER	CM10905	CM11005	CL10905	CL11005
OPTIONAL SUSPENSION				
OPTION	G50	—	—	—
PAYLOAD (Maximum lbs.) ¹	1846	—	—	—
GVWR (lbs.)	5400	—	—	—
GAWR (lbs.) Front Rear	2800 2900	— —	— —	— —
FRONT SUSPENSION				
Type	Ind. Coil Spring	—	—	—
Standard Spring Capacity (Total lbs.)	2800	—	—	—
Front Shock Absorbers Piston Diameter (mm)	32	—	—	—
Front Stabilizer Bar Diameter (in.)	1.10	—	—	—
REAR SUSPENSION				
Type	Composite Leaf Spring	—	—	—
Standard Spring Capacity (Total lbs.)	2900	—	—	—
Leaves Per Spring	1	—	—	—
Leaf Total Thickness (in.)	.906	—	—	—
Rear Shock Absorbers Piston Diameter (mm)	32	—	—	—
FRONT AXLE				
Type	—	—	—	—
Make	—	—	—	—
Maximum Capacity (lbs.)	2800	—	—	—
Standard Hub Locks	—	—	—	—
Pinion/Ring Gear Type	—	—	—	—
REAR AXLE				
Type	Semi-Floating	—	—	—
Make	GM	—	—	—
Maximum Capacity (lbs.)	3150	—	—	—
Pinion/Ring Gear Type	Hypoid	—	—	—
STANDARD TIRES				
Type	Tubeless AS/SBR P205/75R15	—	—	—
Capacity (lbs.) each	1453	—	—	—
Inflation (psi) maximum	35	—	—	—
Revolutions per mile @ 45 mph	769	—	—	—
WHEELS				
Size (in.) Front/Rear	15.0 x 6.0	—	—	—
Capacity (lbs.) each	1575	—	—	—
Bolt Holes	5	—	—	—
Bolt Circle Dia. (in.)	5	—	—	—
Offset (mm)	13	—	—	—

¹Based on Curb Weight.

ASTRO CARGO VAN

WHEELS AND TIRES/ STEERING/BRAKES

KEY: — - Not Available BW - Blackwall
 AS - All-Season WW - Whitewall
 SBR - Steel-Belted Radial Ply WL - White Lettered

WHEELS AND TIRES

TIRE SIZE	TYPE	RPO	PLY	LOAD RANGE	TIRE CAPACITY (lbs.) ea.	INFLATION (psi) max.	WHEEL SIZE (in.)	WHEEL CAPACITY (lbs.) ea.	BOLT HOLES	BOLT CIRCLE dia. (in.)	OFFSET (mm)	REV.PER mile @ 45 mph
P205/75R15	AS/SBR/BW	QCE	—	—	1453	35	15.0 x 6.0	1453	5	5	13	769
P215/75R15	AS/SBR/BW	QCU	—	—	1583	35	15.0 x 6.0	1575	5	5	13	753
P215/75R15	AS/SBR/WW	QCV	—	—	1583	35	15.0 x 6.0	1575	5	5	13	753
P215/75R15	AS/SBR/WL	QCW	—	—	1583	35	15.0 x 6.0	1575	5	5	13	753

OPTIONAL WHEELS

RPO	DESCRIPTION	WHEEL SIZE (in.)	CAPACITY (lbs.) ea.	BOLT HOLES	BOLT CIRCLE dia. (in.)	OFFSET (mm)
ZJ7	Wheels—Rally (Included w/FE3 Suspension; Rally Wheels Include Special Hub Caps and Trim Rings)	15.0 x 6.5	1575	5	5	10

MODEL	ASTRO CARGO VAN	ASTRO EXTENDED CARGO VAN	ASTRO ALL-WHEEL DRIVE CARGO VAN	ASTRO ALL-WHEEL DRIVE EXT. CARGO VAN
MODEL NUMBER	CM10905/ZW9	CM11005/ZW9	CL10905/ZW9	CL11005/ZW9

STEERING


Type	Variable Ratio Integral/Power	Variable Ratio Integral/Power	Variable Ratio Integral/Power	Variable Ratio Integral/Power
Steering Ratio on Center/At lock	16/13:1	16/13:1	16/13:1	16/13:1
Turning Diameter Curb-To-Curb (ft.)	39.5	39.5	40.5	40.5
Wall-To-Wall (ft.)	40.5	40.5	41.5	41.5

BRAKES

GVWR (lbs.)	5000	5400	5600	5800	5850
Type	Vac. Power Front Disc/Rear Drum with Rear-Wheel Anti-Lock System		Vac. Power Front Disc/Rear Drum with Rear-Wheel Anti-Lock System	Hyd. Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System	Hyd. Power Front Disc/Rear Drum with 4-Wheel Anti-Lock System
Booster Diaphragm Diameter (in.)	—	7.9 x 7.9 Tandem	7.9 x 7.9 Tandem	Hydra-boost	Hydra-boost
Front Rotor Size Diameter x Thickness (in.)	11.86 x 1.04		11.86 x 1.04	11.57 x 1.25	11.57 x 1.25
Front Facing Contact Per Axle (sq. in.)	37.92		37.92	34.8	34.8
Rear Drum Size Diameter x Width (in.)	9.5 x 2.0		9.5 x 2.0	9.5 x 2.0	9.5 x 2.0
Rear Facing Contact Per Axle (sq. in.)	63.73		63.73	63.73	63.73
Parking Brake Type	Cable To Rear Wheels		Cable To Rear Wheels	Cable To Rear Wheels	Cable To Rear Wheels

MODEL	ASTRO CARGO VAN (ALL MODELS)		
MODEL NUMBER	CM10905/ZW9	CM11005/ZW9	CL10905/ZW9 CL11005/ZW9
ELECTRICAL			
ENGINE	4.3L V6/4.3L H.P. V6		
STANDARD BATTERY			
Cold Cranking Amps @ 0°F		630	
@ -20°F		470	
Reserve Capacity Minutes @ 80°F		115	
STANDARD ALTERNATOR			
Max. Capacity (Amps)		100	
Max. Watts @ 12 Volts		1200	
Nominal Amp @ Idle approximately		36	
Drive Pulley Ratio		3.2:1	
Model Number		CS130	

ALTERNATOR CURVE




COOLING

MODEL	ASTRO CARGO VAN (ALL MODELS)	
MODEL NUMBER	CM10905/ZW9	CM11005/ZW9 CL10905/ZW9 CL11005/ZW9
STANDARD COOLING SYSTEM		
ENGINE	4.3L V6	4.3L H.P. V6
Radiator Thickness (in.)	.93	1.36
System Capacity (gal.)	3.4	3.4
Fan-No. Blades x Diameter x Pitch (in.)	3 x 18 x 2.72	3 x 18 x 2.72
OPTIONAL COOLING SYSTEMS		
OPT. H.D. RADIATOR	V01 ¹	—
Radiator Thickness (in.)	.93	—
System Capacity (gal.)	3.4	—
Fan-No. Blades x Diameter x Pitch (in.)	5 x 19 x 2.64	—
OPT. AIR CONDITIONING	C60 ²	C60
Radiator Thickness (in.)	.93	1.36
System Capacity (gal.)	3.4	3.4
Fan-No. Blades x Diameter x Pitch (in.)	5 x 19 x 2.64	5 x 19 x 2.64
OPT. H.D. RADIATOR AND TRANS. OIL COOLER	V02	—
Radiator Thickness (in.)	.93	—
System Capacity (gal.)	3.4	—
Fan-No. Blades x Diameter x Pitch (in.)	5 x 19 x 2.64	—

¹ N/A V02 Cooling. Included w/C60 Air Conditioning. ² w/o V02 Cooling, Includes V01 Cooling.

MODEL		ASTRO CARGO VAN	ASTRO EXTENDED CARGO VAN	ASTRO ALL-WHEEL DRIVE CARGO VAN	ASTRO ALL-WHEEL DRIVE EXTENDED CARGO VAN
MODEL NUMBER		CM10905/ZW9	CM11005/ZW9	CL10905/ZW9	CL11005/ZW9
EXTERIOR DIMENSIONS					
BODY					
Wheelbase (in.)	WB	111.0	111.0	111.0	111.0
Overall Length (in.)	OAL	176.8	186.8	176.8	186.8
Overall Height (in.) Nominal	OAH	74.5	74.5	74.5	74.5
Maximum Width (in.)	OAW	77.5	77.5	77.5	77.5
Bumper To Axle (in.) Front	BA	30.6	30.6	30.6	30.6
Rear		35.2	45.2	35.2	45.2
Ground to Top of Rear Load Floor (in.)	GF	25.0	25.0	25.0	25.0
Ground Clearance (in.) Front	—	7.8	7.8	7.6	7.6
Rear		7.3	7.3	7.3	7.3
Side Load Door Opening Height (in.)	—	44.5	44.5	44.5	44.5
Opening Width (in.)	—	34.5	34.5	34.5	34.5
Rear Load Doors Opening Height (in.)	DH DW	44.7	44.7	44.7	44.7
Opening Width (in.)		57.0	57.0	57.0	57.0
Step Up Height (in.) Front Door		16.3	16.3	16.3	16.3
Side Load Door		17.4	17.4	17.4	17.4
SIGN PANEL AREA					
Side Panel (in.)	Shaded Area	46 x 78	46 x 88	46 x 78	46 x 88
Front Door (in.)		18 x 40	18 x 40	18 x 40	18 x 40
INTERIOR DIMENSIONS					
Head Room (in.)	HR	39.2	39.2	39.2	39.2
Leg Room (in.)	LR	41.6	41.6	41.6	41.6
Shoulder Room (in.)	SR	64.0	64.0	64.0	64.0
Hip Room (in.)	HP	65.0	65.0	65.0	65.0
Load Floor Length (in.) To Console w/Front Seat	LFL	116.6	126.6	116.6	126.6
		88.9	98.9	88.9	98.9
Interior Height	IH	47.5	47.5	47.5	47.5
Interior Width (in.) Between Wheelhousings	IWW	51.6	51.6	51.6	51.6
Cargo Volume (cu. ft.) Std.	CV	181.5	200.1	181.5	200.1
Cargo Volume (cu. ft.) 2-Pass.	CV	151.8	170.4	151.8	170.4
FUEL TANK					
Standard Tank (gal.) Approx.		27	27	27	27
Location of Tank		Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle	Between Frame Rails Forward of Rear Axle
Location of Filter		Left Side	Left Side	Left Side	Left Side



ASTRO CARGO VAN

KEY S - Standard 1. Astro Cargo Van (CM10905)
 O - Optional 2. Astro Extended Cargo Van (CM11005)
 — Not Available 3. Astro All-Wheel Drive Cargo Van (CL10905)
 4. Astro All-Wheel Drive Extended Cargo Van (CL11005)

NOTE: Refer to Dealer Order Guide for Updated Option Availability.

OPTION	CODE	DESCRIPTION	RESTRICTIONS	MODELS			
				2-WHEEL DRIVE		ALL-WHEEL DRIVE	
				1	2	3	4
AIR CONDITIONING	C60	w/o V02 Cooling Incls V01 Cooling.		O	O	O	O
AXLE, REAR	G80	Locking Differential		O	O	O	O
BUMPER EQUIPMENT	VE6	Bumpers, Front and Rear Color-Keyed w/Rub Strip		O	O	O	O
COLD CLIMATE PACKAGE	V10	Incls Eng Block Heater and Coolant Protection		O	O	O	O
CONSOLE, ROOF	DK6		Reqs TR9 Lighting	O	O	O	O
CONVENIENCE GROUP	ZQ2	Incls Power Windows and Power Door Locks		O	O	O	O
	ZQ3	Incls Comfortilt Steering Wheel and Electronic Speed Control		O	O	O	O
COOLING SYSTEM	KC4	Incl w/Z82 Trailering	Reqs V01 or V02 Cooling	O	O	O	O
	V01	Incl w/C60 Air	N/A V02 Cooling	O	O	O	O
	V02	Incl w/Z82 Trailering		O	O	O	O
DOOR LOCK SYSTEM, POWER	AU3	Incl w/ZQ2 Conv Pkg		O	O	O	O
ENGINES		(See Powertrains)					
	4.3-liter EFI V6	LB4		S	S	—	—
4.3-liter H.P. CPI V6	L35		O	O	S	S	
GLASS ARRANGEMENTS		See Drawings on Page 3 for Glass Arrangements		O	O	O	O
	Complete Body	ZW6		O	O	O	O
	Rear Panel Doors	ZW2		O	O	O	O
Sliding Door and Rear Panel Doors	ZW3		O	O	O	O	
GLASS, SWING-OUT	A18	Rear Doors and Side Door	Reqs ZW3 or ZW6 Glass	O	O	O	O
GLASS TINTING	AJ1	Deeply Tinted	Reqs ZW2, ZW3, or ZW6 Glass	O	O	O	O
GRILLE	TL1	Deluxe Black w/Argent Highlights		O	O	O	O
HEATER	C36	Rear		O	O	O	O
INSTRUMENTATION, ELECTRONIC	U52	Illuminated		O	O	O	O
LIGHTING, AUXILIARY	TR9	Incls Front & Rear Dome and Reading Lamps, Courtesy Light Switches on all Doors, Front and Rear; Stepwell Lights and a Glove Box Light	Reqs ZX2 Seating	O	O	O	O
MIRRORS				O	O	O	O
	Exterior, Below-Eye-Line Type	D44	Black, L.H. 5" x 8.5" R.H. 5 1/4" x 9" (Convex)	O	O	O	O
Exterior, Electric Remote	D48	Black, L.H. 5" x 8.5" R.H. 5 1/4" x 9" (Convex)		O	O	O	O
PAINTS, EXTERIOR		(See Color and Trim)		S	S	S	S
Solid	ZY1						

ASTRO CARGO VAN

KEY S - Standard
 O - Optional
 — Not Available

1. Astro Cargo Van (CM10905)
 2. Astro Extended Cargo Van (CM11005)
 3. Astro All-Wheel Drive Cargo Van (CL10905)
 4. Astro All-Wheel Drive Extended Cargo Van (CL11005)


NOTE: Refer to Dealer Order Guide for Updated Option Availability.

OPTION	CODE	DESCRIPTION	RESTRICTIONS	MODELS			
				2-WHEEL DRIVE		ALL-WHEEL DRIVE	
				1	2	3	4
RADIO EQUIPMENT							
Electronically-Tuned AM/FM Stereo Radio w/Seek-Scan and Digital Clock	UM7	14 Presets, Digital Display, Two 6" x 9" ERS Front Speakers, 13 Watts Total Power Output.		O	O	O	O
Electronically-Tuned AM/FM Stereo Radio w/Seek-Scan, Stereo Cassette Tape and Digital Clock	UM6	14 Presets, Digital Display, Two 6" x 9" ERS Front Speakers, 13 Watts Total Power Output.		O	O	O	O
Radio Delete	UL5			O	O	O	O
SEATING ARRANGEMENTS							
1 Person Seating	ZX1	1 Front High-Back Bucket, Driver Only in Two Colors	Reqs VDD4 or VSS4 Trim	S	S	S	S
2 Person Seating	ZX2	2 High-Back Bucket Seats in Four Colors		O	O	O	O
SEAT BACK RECLINER AND DUAL ARMRESTS	A78		Reqs ZX2 Seating	O	O	O	O
SPRINGS	G50	Rear, Heavy-Duty Capacity 1450-lbs. each		O	—	—	—
STORAGE COMPARTMENT Drawer-Type Non-Locking	BA8	Located under front passenger seat	Reqs ZX2 Seating	O	O	O	O
TIRE EQUIPMENT		All-Season Steel-Belted Radial Tires (See Wheels and Tires for Details)					
P205/75R15 BW	QCE			S	—	—	—
P215/75R15 BW	QCU			—	S	S	S
P215/75R15 WW	QCV			—	O	O	O
P215/75R15 WL	QCW			—	O	O	O
SPECIAL TRAILERING EQUIPMENT		(See Trailering for Details)					
Heavy-Duty	Z82	Incls V02 and KC4 Engine Oil Cooler; Incls Weight-Distributing Hitch Platform and 7-Wire Wiring Harness and Heavy-Duty Flasher	CM10905 and CM11005 Req GU6 or GT4 Rear Axle; CL10905 and CL11005 Req GT4 Rear Axle	O	O	O	O
Light-Duty	Z72	Incls Deadweight Trailer Hitch, 5-Wire Wiring Harness and Heavy-Duty Flasher	Reqs V01 or V02 Cooling	O	O	O	O
TRANSMISSIONS		(See Powertrains)					
4-Speed Automatic w/Overdrive	MX0			S	S	S	S
WHEELS							
Rally	ZJ7	15.0" x 6.5" Steel Wheel		O	O	O	O

SOLID COLORS

(ZY1)

Solid paint (ZY1) is standard on all models. All painted areas of the body and front-end sheet metal, including the bumpers, are the same color. Below are the interior trim colors and exterior paint combinations recommended by Chevrolet. However, any available interior trim color may be ordered. For further information, refer to Seats and Interior Trim pages as well as the Ordering Guide.



KEY: • Recommended Blank—Available N/A— Not Available


EXTERIOR COLORS		WHEEL COLORS		INTERIOR COLORS		
COLOR CODE 1	COLOR CODE 2	RALLY	Blue	Garnet	Beige	Gray
10 Ivory White	10 Ivory White	Silver	•	•	•	•
15 Sterling Silver Met.	15 Sterling Silver Met.	Silver	•	•		•
16 Fieldstone Gray Met.	16 Fieldstone Gray Met.	Silver		•		•
27 Smoke Blue Met.	27 Smoke Blue Met.	Silver	•			•
30 Catalina Blue Met.	30 Catalina Blue Met.	Silver	•			•
34 Light Teal Met.	34 Light Teal Met.	Silver				•
41 Onyx Black	41 Onyx Black	Silver	•	•	•	•
57 Sand Beige	57 Sand Beige	Beige		•	•	
75 Deep Red Met.	75 Deep Red Met.	Silver		•	•	
76 Burnt Red Met.	76 Burnt Red Met.	Silver		•	•	•

¹ N/A with ZJ7 wheels.

SPECIAL TRAILERING PACKAGES

If you tow a light trailer (up to 2000 lbs. gross weight) with your new Astro Cargo Van, Special Trailering Package (RPO Z72) is recommended. RPO Z72 includes a deadweight hitch which is bolted to the rear bumper and includes a 1 7/8"-diameter hitch ball. This package also includes a 5-wire wiring harness that requires a connector. This allows the electrical system to activate trailer lights and other electrical systems.

If you intend to tow a medium weight trailer (2000 to 4000 lbs. gross weight) or a heavy trailer (4000 to 6000 lbs. gross weight), the heavy-duty Special Trailering Package RPO Z82 is a required option. (This Z82 option is also required, regardless of gross trailer weight, if your trailer tongue weight exceeds 200 lbs.) RPO Z82 includes a weight-distributing hitch platform which is bolted to the undercarriage. RPO Z82 includes a 7-wire wiring harness that requires a connector. With either trailering package, the wiring harness comes coiled and tied, with connecting end stored on the floor in the right-hand rear corner.



See the chart below for trailering options in addition to Special Trailering Packages.

The chart below indicates the trailering equipment required for light, medium and heavy trailer towing. Additional recommended options are also indicated. To help you in ordering, each column lists Regular Production Option (RPO) numbers.

Note: Other important trailering information is available in the Owner's Manual of every 1992 Astro Cargo Van.

(R) — Required

REQUIRED/RECOMMENDED TRAILERING EQUIPMENT						
Hitch Type	Ball					
	Light		Medium		Heavy	
Trailer Classification	2000		4000		6000	
Maximum Trailer Weight (lbs.)	200		500		750	
Maximum Tongue Load (lbs.)	200		500		750	
Vehicle Series	2WD	AWD	2WD	AWD	2WD	AWD
Engine and Axle Ratio with (Maximum Trailer Weight)	4.3L		3.23		3.42	
	3.23	3.42	3.23	3.42	3.42 (5500)	3.42 (5500)
					3.73 (6000)	3.73 (6000)
Special Trailering Package*	Z72	Z72	Z82(R)	Z82(R)	Z82(R)	Z82(R)
Trailer Hitch	Deadweight		—		—	
	Z72	Z72	—	—	—	—
(Weight Distributing) Platform	—		Z82(R)		Z82(R)	
Wiring Harness	5 wire		—		—	
	Z72	Z72	—	—	—	—
	7 wire		Z82(R)		Z82(R)	
Cooling	H.D. Radiator		—		—	
	VO1(R)	VO1(R)	—	—	—	—
	Transmission Oil		Z82(R)		Z82(R)	
	—	—	Z82(R)	Z82(R)	Z82(R)	Z82(R)
	Engine Oil		Z82(R)		Z82(R)	
	—	—	Z82(R)	Z82(R)	Z82(R)	Z82(R)
Locking Rear Axle	—		G80		G80	
	—	—	G80	G80	G80	G80
Cruise Control & Tilt Wheel	—		ZQ3		ZQ3	
	—	—	ZQ3	ZQ3	ZQ3	ZQ3

Trailering Related Standard Equipment:

Power Steering, Power Brakes, 27 Gallon Fuel Tank, 100 Amp Alternator, Heavy Duty Shocks, Front Stabilizer Bar, 4-Speed Automatic Transmission.

* Z82 Available only with 3.42 Axle (3.73 in AWD Models)

HOW TO USE GCWRs TO DETERMINE POWERTRAIN AND REAR AXLE RATIOS FOR TRAILERING

Use Gross Combination Weight Ratings (GCWRs) to determine the engine, transmission and rear axle ratio you will require to tow a trailer with your truck. The chart below shows you the maximum allowable GCWR based on all the available truck engines and rear axle ratios with automatic transmission.

The GCWR includes the total loaded weight of both the truck and trailer. Any available engine may be used for trailering if the GCWR shown is not exceeded. The trailer weight can be increased by 25% if the vehicle speed will not exceed 25 mph.

GROSS COMBINATION WEIGHT RATING (GCWR)																				
With Automatic Transmission																				
GCWR (lb.)	6000	6500	7000	7500	8000	8500	9000	9500	10,000	10,500	11,000	11,500	12,000	12,500	13,500	14,000	14,500	15,000	16,000	19,000
Engines	Rear Axle Ratios																			
4.3L (262) V6 Gas							3.23	3.42	3.73											

When towing a trailer in excess of 4000 lbs. with a truck equipped with a 4-speed automatic transmission, it is recommended to shift to third gear range ("D") instead of overdrive ("O") for normal towing, and to manually downshift as required on uphill and downhill grades.

Note: Model and driveline combinations must be verified by your local dealer for correct emissions equipment.

GENERAL TRAILERING INFORMATION

Chevrolet offers a wide selection of available options for trailering and a few of them are described here.

HITCH BALLS

1 7/8"-diameter ball is standard with light-duty hitches.

WIRING HARNESES

5-wire used with trailers up to 2000 lbs. gross weight and 7-wire for larger trailers. Harnesses tie into vehicle's electrical system to give your trailer lights, plus electric brakes or battery charging.

TRUCK WIRING CODE

The following color code for trucks should be used when installing trailer wiring harnesses.

- **Blue.** Used for electric trailer brakes or auxiliary wiring.
- **Red.** Used for battery charging. Connects to starter solenoid. (7-wire harness only.)
- **Light Green.** Backup lights (7-wire harness only.)
- **Brown.** Taillight and running lights.
- **Yellow.** Left stop and turn signal.
- **Dark Green.** Right stop and turn signal.
- **White.** Ground.

COOLERS AND COOLING

Trailering creates higher-than-normal temperatures in coolant, engine and transmission oil. To help control these temperatures, consider the following separate options.

RPO V02. This is an extra-capacity heavy-duty automatic transmission oil cooler option. (Included in RPO Z82 Special Trailering Package.)

RPO KC4. This optional engine oil cooler circulates oil through a separate cooler mounted LH side of the radiator. (Included in RPO Z82 Trailering Package.)

A


'92 CHEVY

ASTRO VAN


INFORMATION UPDATE



Extended-Body Astro in Smoke Blue Metallic with optional mid-level CL trim. The Astro CL's embellishments include Rally Wheels, an air dam with fog lamps, swing-out glass in the sliding side door and in the dual rear doors, black wheel-opening moldings, black body-side moldings with chrome inserts, and the buyer's choice of Custom Vinyl or Custom Cloth seats.



The LT (Luxury Touring) trim level is Astro's finest optional trim. It includes plush velour upholstery on wide, contoured, aircraft-style front bucket seats. The seat shown is an optional six-way power driver seat with a reclining seat-back that allows precise manual adjustments to seat height and angle.





The towing, hauling, people-moving "van that can" — now with new rear door option.

A new-for-'92 rear door option for all Astro models features a one-piece lift-glass for enhanced rearward visibility and easy loading and unloading of small items. Below the lift-glass are two individual half-doors that can be opened when the lift-glass is in the "up" position.

Astro comes in rear-wheel-drive and All-Wheel-Drive (AWD) models. It's the long-lasting, mid-size van that can do more things better than any non-GM mid-size van — including people-carrying, cargo-hauling (payload) and trailer-towing. No other van uses more corrosion-resistant, two-side-galvanized steel body panels in its construction. The '92 Astro also has GM's Bumper to Bumper Plus, 3-year/36,000-mile, no-deductible, limited warranty. See your Chevy dealer for terms and conditions of this limited warranty.

A 4-wheel anti-lock brake system (ABS) is standard equipment in all '92 Astro models. ABS automatically controls pressure to the power brakes to minimize wheel lockup, whether the driver is braking on a straight, hardtop road or on a curve in the road. In addition to improving vehicle stability during braking, ABS also helps maintain the driver's ability to steer around obstacles, even during hard braking on wet surfaces.





Optional mid-level Astro CL Custom Cloth interior in Blue, with optional rear-row bench seat and 8-passenger seating. Or choose standard seating for 5, or optional 7-passenger seating with center-row bucket seats. With center- and rear-row seats removed, the Extended-Body Astro has 170.4 cu. ft. of cargo space.

PREFERRED EQUIPMENT GROUPS

	1	2	3	4	5
GROUP 1					
Seating: 5-passenger ¹	■	■			
GROUP 2 (Up To \$650 Savings)					
Air Conditioning: Front ¹		■	■	■	■
Glass: Complete body (incl. in Astro LT)		■	■	■	■
Mirrors: Exterior, Below Eyeline ¹		■	■	■	■
Radio: AM/FM stereo with seek-scan and digital clock ¹		■	■	■	■
GROUP 3 (Up To \$850 Savings)					
Convenience Group: Tilt-Wheel™ Adjustable Steering				■	■
Column and electronic speed control		■	■	■	■
Seating: 8-passenger ¹			■	■	■
Reclining Seat-Back and Dual Armrests (incl. in Astro LT)			■	■	■
GROUP 4 (Up To \$1300 Savings)					
Convenience Group: Power windows and power door locks				■	■
Mirrors: Exterior, electric remote				■	■
Radio: AM/FM stereo with seek-scan, cassette tape player and digital clock ¹				■	■
Storage Compartment: Drawer type, nonlocking				■	■
Tires: P205/75R-15 white-lettered (w/o FE3 Suspension; 2WD Astro only)				■	■
Tires: P215/75R-15 white-lettered (w/o FE3 Suspension; excludes 2WD Regular-Body Astro)				■	■
GROUP 5 (Up To \$1500 Savings)					
Luggage Carrier: Black				■	■
Roof Console				■	■
Power Seat: Driver's six-way				■	■
Seating: 7-passenger ¹				■	■
Wheels: Cast-aluminum				■	■




Standard 5-passenger seating.



Optional 7-passenger seating.



Optional 8-passenger seating.



An optional, new-for-'92 AM/FM stereo with seek-scan and compact disc player provides excellent sound fidelity for Astro travelers.

¹Upgrade allowed. NOTE: See your Chevy dealer for Preferred Equipment Groups for the Astro Sport. These convenient option packages make it easy to tailor the Astro Van to your exact specifications and can save you money. You would pay appreciably more buying all the options in a Preferred Equipment Group as individual options. (Savings based on comparison of Manufacturer's Suggested Retail Price of option packages vs. MSRP of individual options purchased separately.)

SPECIFICATIONS

	2WD Regular-Body	2WD Extended-Body	AWD Regular-Body	AWD Extended-Body
GVW Rating (lbs.) ¹	5700	5950	5950	6100
Payload Range (lbs.) ²	1757-1791	1930-1957	1626-1769	1841
Std. Gas Engine w/EFI ³ — Liters/Horsepower	4.3/160 V6	4.3/160 V6	4.3/200 V6	4.3/200 V6
Opt. Gas Engine w/EFI ³ — Liters/Horsepower	4.3/200 V6	4.3/200 V6	—	—
Max. Gross Trailer Weight (lbs.) — Light/Medium/Heavy Trailer Classifications	2000/4000/6000	2000/4000/6000	2000/4000/6000	2000/4000/6000
Max. Tongue Load (lbs.) — Lt./Med./Heavy	200/500/750	200/500/750	200/500/750	200/500/750
Brakes — Front Disc/Rear Drum	Power Hydro-Boost	Power Hydro-Boost	Power Hydro-Boost	Power Hydro-Boost
Anti-Lock Brake System	Four-Wheel	Four-Wheel	Four-Wheel	Four-Wheel

¹Gross Vehicle Weight includes vehicle, passengers, equipment and cargo. ²Payload includes passengers, equipment and cargo. Higher payloads require optional equipment. Payload ratings are based on 1992 Licensing Data, and reflect all available engines. ³Electronic Fuel Injection.