

P30 FORWARD CONTROL CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

New for 1993 is a redesigned steel body Step-Van model.

P30 CUTAWAY VAN

The vehicles that are included in this category are all new for 1993. They include the P30 HI-CUBE VAN, the P30 COMMERCIAL CUTAWAY VAN, the P30 SCHOOL BUS CUTAWAY VAN and the P30 MOTOR HOME CUTAWAY VAN. These vehicles are available in a variety of wheelbases and GVWRs.

- Motor Home Cutaway Van comes with a 7.4L engine standard and the availability of a wheelbase of 158.5," 178," 190" and 208" with a choice of 10,500-lbs, 11,000-lbs, 11,800-lbs, 12,300-lbs, and 14,500-lbs. GVWR.
- Commercial Cutaway Van comes with a 5.7L engine standard and the availability of a wheelbase of 125," 133," 157" and 178" with a choice of 10,100-lbs, 11,000-lbs, 12,000-lbs, and 14,100-lbs. GVWR.
- School Bus Cutaway Van comes with a 5.7L engine standard and the availability of a wheelbase of 125," 133" and 157" with a choice of 11,500-lbs. and 14,500-lbs. GVWR.
- Hi-Cube Van comes with a 5.7L engine standard and the availability of a wheelbase of 133," 157" and 178" in either an aluminum or fiberglass body with a choice of 10,100-lbs, 11,000-lbs, 12,000-lbs. and 14,100-lbs. GVWR.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

MODEL SELECTION SUMMARY

Use the chart below to choose the model that fits your needs. Note that the Maximum Payload is based on curb weight. Also, the Maximum Gross Trailer Weight is based on vehicles that are properly equipped. See your 1993 Chevrolet Truck Order Guide for details.

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD LOAD (LBS.) PROPERLY EQUIPPED
P30 FORWARD CONTROL CHASSIS								
125-INCH WHEELBASE SINGLE REAR WHEELS	CP30842/ZW9	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	4242	—
	CP30842/ZW9/ YYM or YYN rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	4821	—
	CP30842/ZW9/ J55/XYN/YYN front tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	5529	—
125-INCH WHEELBASE DUAL REAR WHEELS	CP30842/ZW9/ J55/R05	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	5381	—
	CP30842/ZW9/ J55/G60 or G51/R05/ YYJ rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	6325	—
	CP30842/ZW9/ J55/G60 or G51/R05/ YYK rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	7322	—
	CP30842/ZW9/ HC7/R05/YSF or YSE rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	7804	—
	CP30842/ZW9/ HC7/R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	9900	—
125-INCH SCHOOL BUS CHASSIS	CP30842/ZW9/ J55/G51/FS3/ B3D/R05	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	11500	3880/7900	7482	—
	CP30842/ZW9/ HC7/FS3/B3D/ R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	14500	5000/11000	9911	—
133-INCH WHEELBASE SINGLE REAR WHEELS	CP31042/ZW9	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	4223	—
	CP31042/ZW9/ YYM or YYN rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	4803	—
	CP31042/ZW9/ J55/XYN/YYN front tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	5511	—
133-INCH WHEELBASE DUAL REAR WHEELS	CP31042/ZW9/ J55/R05	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	5362	—
	CP31042/ZW9/ J55/G60 or G51/R05/ YYJ rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	6306	—
	CP31042/ZW9/ J55/G60 or G51/R05/ YYK rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	7304	—

See the following page for additional P30 Forward Control Chassis Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD LOAD (LBS.) PROPERLY EQUIPPED
P30 FORWARD CONTROL CHASSIS (CONT.)								
	CP31042/ZW9/ HC7/R05/YSF or YSE rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	7785	—
	CP31042/ZW9/ HC7/R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	9881	—
133-INCH SCHOOL BUS CHASSIS	CP31042/ZW9/ J55/G51/FS3/ B3D/R05	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	11500	3880/7900	7309	—
	CP31042/ZW9/ HC7/FS3/B3D/ R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	14500	5000/11000	9846	—
157-INCH WHEELBASE SINGLE REAR WHEELS	CP31442/ZW9	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	4115	—
	CP31442/ZW9/ YYM or YYN rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	4694	—
	CP31442/ZW9/ J55/XYN/YYN front tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	5402	—
157-INCH WHEELBASE DUAL REAR WHEELS	CP31442/ZW9/ J55/R05	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	5254	—
	CP31442/ZW9/ J55/G60 or G51/R05/ YYJ rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	6198	—
	CP31442/ZW9/ J55/G60 or G51/R05/ YYK rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	7195	—
	CP31442/ZW9/ HC7/R05/YSF or YSE rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	7677	—
	CP31442/ZW9/ HC7/R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	9773	—
157-INCH SCHOOL BUS CHASSIS	CP31442/ZW9/ J55/G51/FS3/ B3D/R05	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	11500	3880/7900	7198	—
	CP31442/ZW9 HC7/FS3/B3D/ R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 6.2L V8/M5/A4	14500	5000/11000	9735	—
178-INCH WHEELBASE DUAL REAR WHEELS	CP31842/ZW9/ R05/YYJ rear tires	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	6129	—
	CP31842/ZW9/R05 G51 or G60/J55	—	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	7131	—
	CP31842/ZW9/ HC7/R05/YSF or YSE rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	7594	—
	CP31842/ZW9/ HC7/R05/YSG rear tires	—	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	9690	—

See the following page for P30 Motor Home Chassis Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD (LBS.) PROPERLY EQUIPPED
P30 MOTOR HOME CHASSIS								
137.0-INCH WHEELBASE	CP31132/ZW9	—	7.4L V8/A4	6.2L V8/A4 Diesel	10500	4300/6200	6367	—
	CP31132/ZW9/ F66/YEA	—	7.4L V8/A4	6.2L V8/A4 Diesel	11,000	4880/6200	6848	—
	CP31132/ZW9/ G50/YEA or YYK	—	7.4L V8/A4	6.2L V8/A4 Diesel	11,800	4300/7500	7648	—
	CP31132/ZW9/ G50/F66/ YEA or YNP	—	7.4L V8/A4	6.2L V8/A4 Diesel	12,300	4880/7500	8130	—
158.5-INCH WHEELBASE	CP31432/ZW9	—	7.4L V8/A4	6.2L V8/A4 Diesel	10500	4300/6200	6247	—
	CP31432/ZW9/ F66/YEA	—	7.4L V8/A4	6.2L V8/A4 Diesel	11000	4880/6200	6729	—
	CP31432/ZW9/ G50/YEA or YYK	—	7.4L V8/A4	6.2L V8/A4 Diesel	11800	4300/7500	7529	—
	CP31432/ZW9/ G50/F66/ YEA or YNP	—	7.4L V8/A4	6.2L V8/A4 Diesel	12300	4880/7500	8010	—
	CP31432/ZW9/HC7/ YNP, YSN or YTN	—	7.4L V8/A4	6.2L V8/A4 Diesel	14500	5000/10000	9905	—
	CP31432/ZW9/ F42/ YNP, YSN or YTN	—	7.4L V8/A4	—	14800	5300/10000	10203	—
178.0-INCH WHEELBASE	CP31832/ZW9/ HC4/YNP or YTN	—	7.4L V8/A4	—	14500	5000/10000	9673	—
	CP31832/ZW9/ F42/YNP, YSN or YTN	—	7.4L V8/A4	—	14800	5300/10000	9971	—
	CP31832/ZW9/ F44/YNP or YTN	—	7.4L V8/A4	—	16000	5500/10500	11035	—
190.0-INCH WHEELBASE	CP31932/ZW9/ HC4/YNP or YTN	—	7.4L V8/A4	—	14500	5000/10000	9588	—
	CP31932/ZW9/ F42/ YNP, YSN or YTN	—	7.4L V8/A4	—	14800	5300/10000	9885	—
	CP31932/ZW9/ F44	—	7.4L V8/A4	—	16000	5500/10500	10950	—
208.0-INCH WHEELBASE	CP32032/ZW9/ HC4/YNP or YTN	—	7.4L V8/A4	—	14500	5000/10000	9565	—
	CP32032/ZW9/ F42/ YNP or YTN	—	7.4L V8/A4	—	14800	5300/10000	9862	—
	CP32032/ZW9/ F44	—	7.4L V8/A4	—	16000	5500/10500	10926	—

Note: Motor Home Chassis Models are for recreational vehicle use only and are not to be used for mounting any type of commercial body. See the following pages for P30 Step-Van Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD LOAD (LBS.) PROPERLY EQUIPPED
P30 STEP-VAN								
10.5-FOOT STEEL BODY								
125-INCH WHEELBASE SINGLE REAR WHEELS	CP30842/E32	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	1540	—
	CP30842/E32/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	2119	—
	CP30842/E32/ J55/XYN/ YYN tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	2827	—
125-INCH WHEELBASE DUAL REAR WHEELS	CP30842/E32/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	2681	—
	CP30842/E32/ J55/G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	3625	—
	CP30842/E32/ J55/G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	4622	—
	CP30842/E32/ HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	5104	—
	CP30842/E32/ HC7/R05/ YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	7200	—
12.5-FOOT STEEL BODY								
133-INCH WHEELBASE SINGLE REAR WHEELS	CP31042/E32	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	1272	—
	CP31042/E32/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	1852	—
	CP31042/E32/ J55/XYN/YYN front tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	2560	—
133-INCH WHEELBASE DUAL REAR WHEELS	CP31042/E32/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	2413	—
	CP31042/E32/J55/ G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	3357	—
	CP31042/E32/ J55/G60 or G51/R05 YYK rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	4355	—
	CP31042/E32/ HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	4836	—
	CP31042/E32/ HC7/R05/YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	6932	—

See the following pages for additional P30 Step-Van Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD LOAD (LBS.) PROPERLY EQUIPPED
P30 STEP-VAN (CONT.)								
14.5-FOOT STEEL BODY								
157-INCH WHEELBASE SINGLE REAR WHEELS	CP31442/E32	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	927	—
	CP31442/E32/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	1506	—
	CP31442/E32/ J55/XYN/YYN front tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	2214	—
157-INCH WHEELBASE DUAL REAR WHEELS	CP31442/E32/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	2068	—
	CP31442/E32/ J55/G60 or G51/R05/ YYJ/rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	3012	—
	CP31442/E32/ J55/G60 or G51/R05/ YYK rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	4009	—
	CP31442/E32 HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/11800	4491	—
	CP31442/E32/ HC7/R05/YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	6587	—
10.5-FOOT ALUMINUM BODY								
125-INCH WHEELBASE SINGLE REAR WHEELS	CP30842/E33	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	2569	—
	CP30842/E33/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	3148	—
	CP30842/E33/ J55/XYN/YYN front tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	3856	—
125-INCH WHEELBASE DUAL REAR WHEELS	CP30842/E33/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	3710	—
	CP30842/E33/ J55/G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	4654	—
	CP30842/E33/ J55/G60 or G51/R05/ YYK rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	5651	—
	CP30842/E33/ HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/11800	6133	—
	CP30842/E33/ HC7/R05/YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	8229	—

See the following pages for additional P30 Step-Van Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD (LBS.) PROPERLY EQUIPPED
P30 STEP-VAN (CONT.)								
12.5-FOOT ALUMINUM BODY								
133-INCH WHEELBASE SINGLE REAR WHEELS	CP31042/E33	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	2475	—
	CP31042/E33/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	3055	—
	CP31042/E33/ J55/XYN/YYN tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	3763	—
133-INCH WHEELBASE DUAL REAR WHEELS	CP31042/E33/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	3617	—
	CP31042/E33/ J55/G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	4561	—
	CP31042/E33/ J55/G60 or G51/R05/ YYK rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	5558	—
	CP31042/E33/ HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	6040	—
	CP31042/E33/ HC7/R05/YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	8136	—
14.5-FOOT ALUMINUM BODY								
157-INCH WHEELBASE SINGLE REAR WHEEL	CP31442/E33	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	7600	3880/4670	2119	—
	CP31442/E33/ YYM or YYN rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	8200	4000/5246	2698	—
	CP31442/E33/ J55/XYN/YYN front tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	4000/6084	3406	—
157-INCH WHEELBASE DUAL REAR WHEELS	CP31442/E33/ J55/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	9000	3880/6200	3260	—
	CP31442/E33/ J55/G60 or G51/R05	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7060	4204	—
	CP31442/E33/ J55/G60 or G51/R05/ YYK rear tires	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	5201	—
	CP31442/E33/ HC7/R05/YSF or YSE rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	5683	—
	CP31442/E33/ HC7/R05/YSG rear tires	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	7207	—

See the following page for additional P30 Step-Van Models.

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SERIES	MODEL NUMBER/ BODY CODE/ OPTION CODE	PASSENGER CAPACITY (STD./OPT.)	STANDARD ENGINE/ TRANS.	OPTIONAL ENGINE/ TRANS.	GVWR (LBS.)	GAWR (LBS.) FRONT/ REAR	MAXIMUM PAYLOAD (LBS.) BASED ON CURB WT.	MAX. GROSS TRAILER WT./ TONGUE LOAD LOAD (LBS.) PROPERLY EQUIPPED
P30 STEP-VAN (CONT.)								
18.0-FOOT ALUMINUM BODY								
178-INCH WHEELBASE DUAL REAR WHEELS	CP31842/E33	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	10000	3880/7900	3929	—
	CP31842/E33	1/2	4.3L V6/M5	4.3L V6/A4 5.7L V8/M5/A4 6.2L V8/M5/A4	11000	4000/7900	4931	—
	CP31842/E33	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	12000	4500/9840	5394	—
	CP31842/E33	1/2	5.7L V8/M5	5.7L V8/A4 7.4L V8/A4 6.2L V8/M5/A4	14100	4500/11000	7490	—

POWERTRAINS

Chevrolet offers a variety of engines, transmissions and rear axle ratios for the P30 Chassis. The following charts detail basic engine, transmission and axle specifications. See your 1993 Chevrolet Truck Order Guide for details.

ENGINES				
	4.3L V6	5.7L V8	7.4L V8	6.2L V8 DIESEL
Order Code	LB4	L05	L19	LL4
Availability	N/A on Motor Home	N/A on Motor Home	All	All
SAE Net Horsepower Horsepower @ rpm	155 @ 4000	190 @ 4000	230 @ 3600	155 @ 3500
SAE Net Torque lbs-ft @ rpm	230 @ 2400	300 @ 2400	380 @ 1600	285 @ 2000
Fuel System	EFI	EFI	EFI	Gear-Driven Mechanical FI
Clutch Size (in.)	11	12	—	12
Standard Battery Cold Cranking Amps at 0°F	630	525	630	2 @ 540 each
Standard Alternator Max. Capacity (Amps)	105	105	105	105

TRANSMISSIONS							
	MANUAL MANUAL 5-SPEED W/OD NP4500				AUTOMATIC AUTOMATIC 5-SPEED W/OD 4L80-E		
Order Code	MM5				MX0		
Availability	N/A on Motor Home				N/A on Motor Home		All
Engine Application (Order Code)	4.3L V6 (LB4)	5.7L V8 (L05)	7.4L V8 (L19)	6.2L V8 Diesel (LL4)	4.3L V6 (LB4)	5.7L V8 (L05)	7.4L V8 (L19) 6.2L V8 Diesel (LL4)
Gear Ratios							
First	6.34				2.48		
Second	3.44				1.48		
Third	1.71				1.00		
Fourth	1.00				0.75		
Fifth	0.73				—		
Reverse	6.34				2.07		

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

REAR AXLES					
Make/Capacity (lbs.)	GM 7900 Full-Floating				Dana 11,000 Full-Floating
	Hypoid				Hypoid
Pinion and Ring Gear Type	Hypoid				Hypoid
Axle Ratio Code	GT4	GT5	HC4	HC7	HC7
Ratio	3.73	4.10	4.56	5.13	5.13
Pinion Teeth	11	10	9	8	8
Ring Gear Teeth	41	41	41	41	41
Ring Gear Diameter (in.)	10.5	10.5	10.5	10.5	11.3

REAR AXLES (P30 MOTOR HOME CHASSIS)							
Make/Capacity (lbs.)	GM 7900 Full-Floating		GM ¹ 10,000 Full-Floating			Dana ³ 10,500 Full-Floating	
	Hypoid		Hypoid			Hypoid	
Pinion and Ring Gear Type	Hypoid		Hypoid			Hypoid	
Engine Availability	All		7.4L V8 (L19) Only			7.4L V8 (L19) Only	All
Axle Ratio Code	GT5	HC4	HC4	HF8	HC7	GK9	HC7
Ratio	4.10	4.56	4.56	4.88	5.13 ²	4.63	5.13
Pinion Teeth	10	9	9	8	8	8	8
Ring Gear Teeth	41	41	41	39	41	37	41
Ring Gear Dia. (in.)	10.5	10.5	10.5	10.5	10.5	11.3	11.3

¹ 14,500 lb. and 14,800 lb. GVWR only. ² Diesel models only. ³ Dana models have tubular section only.

TRIM LEVELS

The following chart details major standard features for F.C. Chassis, Step Van, and Motor Home. See your 1993 Chevrolet Truck Order Guide for more details.

CHASSIS EQUIPMENT				
KEY: ■ = STANDARD, — = NOT INCLUDED		F.C. CHASSIS	STEP VAN	MOTOR HOME
BRAKES	Power vacuum front disc/rear drum brakes up to 12000-lb. GVWR; power hydraulic front and rear disc 12000-lb. and above GVWR. Power hydraulic front disc/rear drum up to 12,300-lb. GVWR; power hydraulic front and rear disc 12,300-lb. and above GVWR.	■	■	—
EXHAUST	Dual.	—	—	■
FRAME	Riveted ladder-type with channel design.	■	■	■
FUEL TANK	40-gallon (approx.) capacity.	■	■	■
REAR AXLE	Hypoid, full-floating. Ratios vary with model.	■	■	■
SHOCK ABSORBERS	Front and Rear—32 mm piston diameter.	■	■	■
STABILIZER BAR	Front—1.25 inch diameter, heavy duty.	■	■	■
STEERING	Integral power.	■	■	■
SUSPENSION	Front—Independent with coil springs. Rear—2-stage Multi-Leaf on all models with ZW9 (except CP31842) and CP30842/E32/E33 and CP31042/E32/E33. Rear—Combination semi-elliptic two stage main-Auxiliary— CP31442/E32/E33. Independent coil with auxiliary air spring.	■	■	■
		—	—	■

EXTERIOR EQUIPMENT				
		F.C. CHASSIS	STEP VAN	MOTOR HOME
BUMPER	Front painted white. Rear step painted black. Front painted argent. Includes bumper guards.	—	■	—
GLASS	Tinted.	—	■	—
GRILLE	Black with bright moldings. Headlamp/parking lamp bezels painted silver on steel vans; black injection molded on aluminum vans.	—	■	—
HORN	Single electric low-note.	■	■	■
LAMPS	Front and rear roof marker lamps.	—	■	—
MIRRORS	White RH and LH arm with two separate adjustable heads, one with flat glass and one with convex glass. Head size 6.5" x 9.0."	—	■	—
WHEEL COVERS	Bright metal with black trim w/R04 only.	—	■	—
WINDOW	LH sliding window.	—	■	—

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

INTERIOR EQUIPMENT

KEY: ■ = STANDARD, — = NOT INCLUDED		F.C. CHASSIS	STEP VAN	MOTOR HOME
DOMELAMPS	Front and rear compartment.	—	■	—
FLOOR COVERING	Rubber mat in drivers' foot control area.	—	■	—
GAGES	Engine temperature, fuel level, odometer, oil pressure, quartz speedometer, trip odometer, voltmeter and additional telltale lights.	■	■	—
PARCEL TRAY	On top of engine housing.	—	■	—
SEAT	Hi-back front bucket driver's seat with vinyl trim.	—	■	—
STEERING WHEEL	2-spoke.	■	■	■
SUNSHADES	Driver's side adjustable tinted plexiglass.	—	■	—
VENT	Outside air with door.	—	■	—

FORWARD CONTROL CHASSIS AND STEP VAN OPTIONS

These options can be ordered individually. See your 1993 Chevrolet Truck Order Guide and Vehicle Price Schedule for specific information and prices.

Air Conditioning (requires E32 or E33 body and L05 engine) (includes 105 amp alternator and heavy-duty cooling) .. **C60**

Alternator, 124 amp (requires L19 engine) .. **KW2**

Axle, Front I-Beam (N/A 7600, 8200, or 9000 GVWR) (N/A L19 engine) (w/J55 brakes requires G51 and C7A/C7C or 11,500 GVWR and XDE, XEA, XSF, XYJ or XYK tires) .. **FS3**

Axle, rear locking differential .. **G80**

Battery, heavy-duty (N/A LL4 diesel engine) .. **UA1**

Brakes, heavy-duty power (std on CP31842) (N/A L19 engine) (available w/HCT rear axle only when LL4 engine and 11,500 GVWR or L05 engine and 11,000 GVWR are specified or w/LB4 and 9,000, 10,000, 11,000 or 11,500 GVW and GQ1 are specified) .. **J55**

Bumper, front
Black (included w/B3M school bus special equipment) .. **VH6**
Extra wide, white (N/A E32 body) .. **VKL**

Cooling system, engine oil (N/A LL4 engine) .. **KC4**

Engines:
4.3L EFI V6 .. **LB4**
5.7L EFI V8 .. **L05**
7.4L EFI V8 .. **L19**
6.2L Gear driven mechanical FI V8 (requires FS3 axle) .. **LL4**
Fender, deletion (requires ZW9 body) .. **FNT**

GVWR Ratings
 7600 .. **C6G**
 8200 .. **C6N**
 9000 .. **C6U**
 10,000 .. **C7A**
 11,000 .. **C7E**
 11,500 .. **C7G**
 12,000 .. **C7L**
 14,100 .. **C7M**
 14,500 .. **C7S**

Heater, engine block (N/A LL4 diesel equipment) .. **K05**

Horn, dual electric (N/A CP31842 or B3D/B3M school bus) .. **U08**

Paint, exterior:
Solid .. **ZY1**

School bus chassis equipment (N/A CP31842) (11,500 and 14,500 GVWR only) (requires FS3 front axle) (w/14,500 GVWR requires HC7 heavy duty rear axle and YSG tires) (w/11,500 GVWR requires R05 wheels G51 springs, J55 brakes) (N/A E32 steel or E33 aluminum body or L19 engine or YYJ tires) (includes brake warning indicator) (includes 105 amp alternator) .. **B3D**

School bus special equipment (requires B3D school bus chassis) (N/A CP31842 or L19 engine) (includes black bumpers and black wheel color) .. **B3M**

Springs, heavy duty front 5,000-lb (10,000, 11,000 or 11,500 GVWR only) (requires FS3 front axle and J55 brakes) .. **F60**

Springs, heavy duty rear (CP30842, CP31042, and CP31442 requires 9,000, 10,000, 11,000 or 11,500 GVWR) (CP31842 requires C7A/C7E GVWR) .. **G51**

Springs, rear main and auxiliary. Capacity 4000-lb each (requires C7A/C7E also requires R05 wheels w/CP30842, CP31042) (N/A 12,000, 14,000 or 14,500 GWR) (N/A w/FS3 front axle) .. **G60**

Suspension, Positrim front heavy duty (requires L05 or LL4 engine) (CP30842, CP31042, CP31442 requires J55 brakes) (N/A HC7 heavy duty axle or B3D school bus equipment or FS3 front axle) .. **F66**

Transmissions:
5-speed manual OD .. **MM5**
4-speed automatic OD .. **MX0**

Wheel color, black (included w/B3M school bus special equipment) .. **41P**

Wheel color, gray (Reqs. R05) (Included with CP31842) .. **84P**

Dual rear (std on CP31842) (w/o HC7 heavy duty axle requires J55 brakes) (CP30842, CP31042, CP31442 w/E32 or E33 body includes wheelhousing) .. **R05**

Single Rear (N/A CP31842) .. **R04**

Wheel, spare 19.5" x 6.00" (requires 8-19.5 tires) (w/E32 or E33 body requires P14 or P15 spare wheel carrier) (included w/spare tires) .. **Q34**

TIRES

KEY: AS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW - BLACKWALL WW = WHITEWALL WL = WHITE LETTERED HWY = HIGHWAY BL = BLACK LETTERED ON-OFF = ON-OFF ROAD WOL = WHITE OUTLINE LETTERED

		FRONT	REAR	SPARE
LT215/85R16C	AS/SBR/BW	XYJ	YYJ	ZYJ
LT215/85R16D	AS/SBR/BW	XYK	YYK	ZYK
LT215/85R16D	ON-OFF/SBR/BW		YYL	ZYL
LT235/85R16D	AS/SBR/BW	XYM	YYM	ZYM
LT235/85R16E	AS/SBR/BW	XYN	YYN	ZYN
7.50-16/LT-D	BW (POLYESTER)	XEA	YEA	ZEA
7.50-16/LT-D	BW	XDE	YDE	ZDE
7.50-16/LT-D	ON-OFF/BW		YDL	ZDL
8-19.5D	BW	XSF	YSF	ZSF
8-19.5D	ON-OFF BW		YSE	ZSE
8-19.5E	BW (REQS. HC7 HEAVY DUTY AXLE)	XSG	YSG	ZSG

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

MOTOR HOME CHASSIS OPTIONS

Alternator, 124 Amp (Reqs L19 Engine) **KW2**
 Axle, Rear: (Must specify one of the following.)
 4.10 Ratio Axle, Heavy Duty **GT5**
 4.56 Ratio Axle, Heavy Duty **HC4**
 4.88 Ratio Axle, Heavy Duty **HF8**
 5.13 Ratio Axle, Heavy Duty **HC7**
 Differential, (locking rear) **G80**
 Engine (Must specify one of the following, refer to Engine Specifications Chart)

Gasoline: V8 7.4 liter (454 Cu In) EFI.. **L19**
 Diesel: V8 6.2 liter diesel H.D. (379 Cu In) **LL4**
 Heater, Engine Block (N/A w/LL4 Engine) **K05**
 HVAC Provision Delete, (Heater ventilation and air conditioning) (Requires L19 engine) **EN2**
 Horn, Dual electric **U08**
 Speed Control Electronic,

(Requires L19 engine) **K34**
 Tank, Fuel:
 Approx. 60-Gallon Capacity (N/A P31132) **NN4**
 Approx. 80-Gallon Capacity L.H. or R.H. Fill (P31832-P31932-P32032 Only) **NJ9**
 Transmission:
 4-Speed Automatic w/Overdrive, Electronic Control. **MX0**
 Wheel, Color, Black **41P**

TIRES				
KEY: AS = ALL-SEASON SBR = STEEL-BELTED RADIAL PLY BW = BLACKWALL WW = WHITEWALL WL = WHITE LETTERED HWY = HIGHWAY BL = BLACK LETTERED ON-OFF = ON-OFF ROAD WOL = WHITE OUTLINE LETTERED				
		FRONT	REAR	SPARE
LT215/85R16C	AS/SBR/BW	—	YYJ	—
LT215/85R16D	AS/SBR/BW	XYK	YYK	ZYK
LT225/70R19.5F	SBR/BW	XTN	YTN	ZTN
8-19.5D HIGHWAY	SBR BW	XNP	YNP	ZNP
7.50-16/LT-D	BW (POLYESTER)	XEA	YEA	ZEA

SPECIAL EQUIPMENT OPTIONS

The following special equipment is installed at the assembly plant. See your 1993 SEO catalog for specific availability and restrictions.

SPECIAL EQUIPMENT OPTIONS (STEP VAN, FORWARD CONTROL AND MOTOR HOME CHASSIS)		
	LEAD TIME (DAYS)	OPTION CODE
Alarm, Engine with Light P3**42 only (available only when RPO LL4 engine and RPO E33 body or RPO ZW9 chassis are specified. Indicates high coolant temperature and low oil pressure).	0	8Y1
Batteries, Dual 630CCA. P3**42 models only (available only when RPO LL4 is specified) (N/A w/RPO B3D school bus equipment. Engine compartment mounted).	0	8Y2
Bumper, Front Extra Wide Black. P3**42 models only (available only when RPO E33 or ZW9 chassis is specified).	0	5K6
Bumper, Delete, Front P3**42 (available only when GVWR is in excess of 11,000 lb and RPO FS3 I-beam front axle is ordered) (N/A when RPO E73 or E74 body equipment is specified).	0	8H5
Doors, Rear Overhead 74" spacesaver (available only when RPO E32 body is ordered) (N/A on Motor Home or P31842).	0	7U3
Fuel Tank Deletion P3**32 models only (available only w/RPO L19 engine is specified).	0	9H2
Generator, 124 amp P3**42 except P31842 (available only when RPO LL4 engine and RPO B3D School Bus Equipment or RPO L05 engine without air conditioning is specified).	0	BA3
Headlamp, Single Rectangular — Motor Home only.	0	BD5
Hooks, Front Tow P3**42 only (available only when RPO E32 or RPO E33 body equipment is specified. N/A when RPO FS3 I-beam front axle is specified).	0	8L2
Hoses, Silicone Radiator and Heater: P3**42 only (available only when either RPO L05 engine and RPO E32 or RPO E33 or LL4 engine is specified).	0	8B7
Lamp, Dome P3**42 only (available only when RPO E32 or RPO E33 body is specified).	0	8J5
Paints: Solid (available with RPO E32 or RPO E33 body). Orange, Tangier WE9417 Yellow, Wheatland WE9418 Green, Woodland WE7156	0 0 0	9W4 9W3 9V5
Spring, Heavy Duty, Rear P3**32 except P31132. Provides rear spring rated at 10,500 lbs.	0	5F8
Stepwell, Non-Skid Front P3**42 only (available only when RPO E32 or RPO E33 body is specified).	0	8G4
Tires: 7.50R—16/D Highway Radial Michelin Tubeless BW.	0 0 0	Front: 2WG Rear: 3WG Spare: 4WG
7.50R—16/D Highway Radial Goodyear Tubeless Black Lettered. P3**42 models only (available only when RPO RO5 dual rear wheels are ordered).	0 0	Front: 2DN Rear: 3DS
8.00R—19.5/E steel belted radial Goodyear Wrangler radial rib tubeless BW. P3**42 models only (available only when RPO RO5 dual rear wheels are ordered).	0 0 0	Front: 2TV Rear: 3TV Spare: 4TV

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

SPECIAL EQUIPMENT OPTIONS (CONT.)		
	LEAD TIME (DAYS)	OPTION CODE
8.00R—19.5/D Steel Belted Radial Michelin Tubeless, BW. P3**42 only. Not available above 12,000-lb. GVW. Available only with RPO R05 dual rear wheels.	0 0 0	Front: 2NP Rear: 3NP Spare: 4NP
LT235/85R16/E Steel Belted Radial On-Off Road, Tubeless, Black lettered. P30842 at 9000-lb. GVW only.	0	Rear: 3YT
8.00R—19.5/E Highway Radial Tubeless, BW. Available only with RPO R05 dual rear wheels and 10,000-lb. GVW.	0 0 0	Front: 2QY Rear: 3QY Spare: 4QY
8.00R—19.5/F Steel Belted Radial Tubeless, Black lettered. P3**42 except P31842. Available only with RPO R05 dual rear wheels.	0 0 0	Front: 2TX Rear: 3TX Spare: 4TX
8.00R—19.5/F Steel Belted Radial All Season, Black Lettered P3**42 except P31842. Available only with RPO R05 dual rear wheels.	0	Rear: 3TW

DIMENSIONS

MODEL	FORWARD CONTROL COMMERCIAL CHASSIS			
	CP30842/ZW9	CP31042/ZW9	CP31442/ZW9	CP10842/ZW9
EXTERIOR DIMENSIONS (P30 FORWARD CONTROL CHASSIS)				
BODY:				
Wheelbase (in.)	125.0	133.0	157.0	178.0
Overall Length (in.) w/o Rear Bumper	214.8	238.8	262.8	318.4
Maximum Width (in.) Steel/Alum.	85.5	85.5	85.5	85.5
Bumper to Axle (in.) Steel Front Alum. Rear	36.0 —	36.0 —	36.0 —	36.0 —
Ground to Top of Rear Load Floor (in.)	27.9	29.1	29.1	29.1
Ground Clearance (in.) Front	9.9 7.2	9.7 7.2	9.7 7.2	9.7 7.2

* School Bus Chassis Dimensions — See Order Guide

MODEL	P30 MOTOR HOME CHASSIS (137-IN. WB)	P30 MOTOR HOME CHASSIS (158.5-IN. WB)	P30 MOTOR HOME CHASSIS (178-IN. WB)	P30 MOTOR HOME CHASSIS (190-IN. WB)	P30 MOTOR HOME CHASSIS (208-IN. WB)
	CP31132/ZW9	CP31432/ZW9	CP31832/ZW9	CP31932/ZW9	CP32032/ZW9
EXTERIOR DIMENSIONS (P30 MOTOR HOME CHASSIS)					
BODY:					
Wheelbase (in.)	137.0	158.5	178.0	190.0	208.0
Overall Length (in.)	234.3	259.4	317.3	329.3	347.3
Bumper to Axle (in.) Front	33.5	33.5	33.5	33.5	33.5
Rear Overhand	63.8	67.4	105.8	105.8	105.8
Overall Width (in.)	85.0	85.0	85.0	85.0	85.0
Frame Width (in.)	34	34	34	34	34
Ground to Top of Frame (in.)	27.9	27.9	30.6	30.6	30.6

P30 F.C. CHASSIS, MOTOR HOME CHASSIS AND STEP-VAN

DIMENSIONS (CONT.)

MODEL	STEP-VAN P3500 STEEL/ALUMINUM 10.5-FT./12.5 FT. (125/133/157-IN. WB)			STEP-VAN P3500 ALUMINUM 18-FT. (178-IN. WB)
	CP30842/E32 CP30842/E33	CP31042/E32 CP31042/E33	CP31442/E32 CP31442/E33	CP31842/E33
EXTERIOR DIMENSIONS (P30 STEP-VAN)				
BODY:				
Wheelbase (in.)	125.0	133.0	157.0	178.0
Overall Length (in.) w/o Rear Bumper	226.8/226.5	250.8/250.4	274.8/274.5	316.5
Overall Height (in.) Steel/Alum.	109.5/110.5	109.5/110.5	109.5/110.5	110.5
Maximum Width (in.) Steel/Alum.	82.5/83.1	82.5/83.1	82.5/83.1	83.1
Bumper to Axle (in.) Front Steel/Alum. Rear	35.9 65.7/64.2	35.9 81.7/80.2	35.9 82.17/80.2	35.9 101.2
Ground to Top of Rear Load Floor (in.)	29.9/28.0	29.9/28.0	29.9	29.9
Ground Clearance (in.) Front/Rear	9.9 7.2	9.9 7.2	9.9 7.2	9.9 7.2
Rear Door Width (in.) STD Steel/Alum.	38/38	38/38	38/38	38/38
OPT Hinge—Steel	60/74	60/74	60/74	60/74
OPT Hinge—Alum.	60/74/83/87	60/74/83/87	60/74/83/87	60/74/83/86
OPT Overhead —Steel/Alum.	66/73	66/73	66/73	66/73
Rear Door Height (in.) STD	69.4/71.2	69.4/71.2	69.4/71.2	69.4

INTERIOR DIMENSIONS (P30 STEP-VAN)				
Load Floor Length (in.) Steel/Alum. Overall Front of Wheelhousing Rear of Wheelhousing	129.6/126.8 65.6/54.9 37.2/30.76	153.6/150.2 63.6/62.9 53.2/46.8	177.6/174.8 87.6/86.9 53.2/46.8	216.8 107.9 67.8
Load Floor Width (in.) Steel/Alum. STD	77.5/77.6	77.5/77.6	77.5/77.6	77.6
Inside Width at Wheelhousing (in.) w/Dual Rear Wheels	48.0 40.0	48.0 40.0	48.0 40.0	— 40.0
Interior Height (in.) Steel/Alum. STD	76/76.2	76/76	76/76.2	76
Cargo Volume (cu.ft.) Steel/Alum. STD	415.5/421.5	496.5/503.5	577.5/585.5	729.1

